

Product data sheet

Specifications



Power cable SH3/MH3 motor to Lexium 52/62 drive, 10mm2, M40, 20m

VW3E1154R200

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	PacDrive 3
Product or Component Type	Cable

Complementary

Range Compatibility	Lexium 52 Lexium 62
Product compatibility	LXM 62 servo drive LXM 52 servo drive SH32052P... SH32053P... MH31902P... MH31903P...
Connector type	M40
Accessory / separate part destination	Temperature sensor Power supply Holding brake
Cable cross section	0.02 in² (10 mm²)
Cable length	65.6 ft (20 m)
Net Weight	39.754 lb(US) (18.032 kg)

Ordering and shipping details

Category	US1PC5218350
Discount Schedule	PC52
GTIN	3606485378503
Returnability	Yes
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	7.087 in (18.000 cm)
Package 1 Width	15.827 in (40.200 cm)
Package 1 Length	17.874 in (45.400 cm)
Package weight(Lbs)	38.003 lb(US) (17.238 kg)

Contractual warranty

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	144 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	106 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	35 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	21
Circularity Profile	End of Life Information
Take-back	No