

Product data sheet

Specifications



Acti9 - OF SD24 auxiliary contact with TI24 interface (bottom)

A9N26898

⚠ Discontinued on: Oct 8, 2021

⚠ Discontinued

Main

range of product	Librio Clario Acti9 Prodis
Product or Component Type	OC and fault contact with PLC interface
Device short name	OF+SD 24
Signal contacts composition	1 NO + 1 NC
Line Rated Current	DC-12 2...100 mA at 24 V, DC +/- 20 %
9 mm pitches	1
Standards	IEC 60947-5-4 IEC 60947-5-1
Quality labels	CE

Complementary

Range compatibility	Acti9 DPN Vigi Acti9 RCCB-ID 125A Acti9 iDPN Vigi Acti9 connectors TI24 Acti9 C60H-DC Acti9 C60PV-DC Acti9 C40 Acti9 ID C40 Acti9 C120 Acti9 DT40 Acti9 DT60 Acti9 IDc
[UI] rated insulation voltage	500 V IEC 60664-1
[Uimp] rated impulse withstand voltage	6 kVIEC 60664-1
Local signalling	Mechanical indicator
Mounting Mode	Fixed
Mounting Support	DIN rail
Height	3.6 in (91 mm)
Width	0.4 in (9 mm)
Depth	2.9 in (73 mm)
color	White
Electrical durability	20000 cycles IEC 60947-5-4
Connections - terminals	Spring-loaded terminal Ti24 bottom) 2 0.0004...0.001 in ² (0.25...0.75 mm ²) - flexible Spring-loaded terminal Ti24 bottom) 1 0.0008...0.002 in ² (0.5...1.5 mm ²) - rigid

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Wire stripping length	0.4 in (10 mm)
-----------------------	----------------

Environment

IP degree of protection	IP20
-------------------------	------

Pollution degree	2 IEC 60664-1
------------------	---------------

Overvoltage category	III
----------------------	-----

Tropicalisation	2 IEC 60947-5-1
-----------------	-----------------

Relative humidity	93 % 104 °F (40 °C)
-------------------	---------------------

Ambient Air Temperature for Operation	-13...140 °F (-25...60 °C)
---------------------------------------	----------------------------

Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
-------------------------------------	----------------------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Nbr. of units in pkg.	1
-----------------------	---



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No