

Product datasheet

Specifications



Control relay, Easy TeSys Control, CAE, 3NO+1NC, ≤690V, 110V AC coil

CAE31F6

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

Main

Range	Easy TeSys
Range of product	Easy TeSys Control Relay
Product or component type	Control relay
Device short name	CAE
Contactors application	Control circuit
Colour	Grey (RAL 7011)

Complementary

Utilisation category	AC-15 AC-14
Pole contact composition	3 NO + 1 NC
[Ue] rated operational voltage	≤ 690 V AC
Control circuit type	AC at 60 Hz
[Uc] control circuit voltage	110 V AC 60 Hz
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947
[Ith] conventional free air thermal current	10 A (at 40 °C)
Irms rated making capacity	140 A at 690 V AC conforming to IEC 60947-5-1
[Icw] rated short-time withstand current	120 A - 500 ms 140 A - 100 ms
Associated fuse rating	10 A gG at 690 V conforming to IEC 60947-5-1
[Ui] rated insulation voltage	690 V conforming to IEC 60947-5-1
Mounting support	Rail Plate
Connections - terminals	Screw clamp terminals 1 1...2.5 mm ² - cable stiffness: flexible without cable end Screw clamp terminals 2 1...2.5 mm ² - cable stiffness: flexible without cable end Screw clamp terminals 1 1...2.5 mm ² - cable stiffness: flexible with cable end Screw clamp terminals 2 1...2.5 mm ² - cable stiffness: flexible with cable end Screw clamp terminals 1 1...2.5 mm ² - cable stiffness: solid without cable end Screw clamp terminals 2 1...2.5 mm ² - cable stiffness: solid without cable end
Recommended tightening torque	1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2
Control circuit voltage limits	Drop-out: 0.3...0.6 U _c Operational: 0.85...1.1 U _c at 60 Hz
Operating time	4...19 ms coil energisation and NC opening 12...22 ms coil energisation and NO closing 4...12 ms coil de-energisation and NC opening 6...17 ms coil de-energisation and NO closing

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mechanical durability	10 Mcycles
Maximum operating rate	180 cyc/mn
Inrush power in VA	70 VA 60 Hz (at 20 °C)
Hold-in power consumption in VA	8 VA 60 Hz (at 20 °C)
Minimum switching voltage	17 V
Minimum switching current	5 mA
Non-overlap time	1.5 ms on energisation between NC and NO contact 1.5 ms on de-energisation between NC and NO contact
Insulation resistance	> 10 MOhm
Mechanical robustness	Shocks control relay open: 7 Gn for 11 ms Shocks control relay closed: 10 Gn for 11 ms Vibrations control relay open: 1.5 Gn, 5...300 Hz Vibrations control relay closed: 3 Gn, 5...300 Hz
Height	74 mm
Width	45 mm
Depth	80 mm
Net weight	0.28 kg

Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-5-1 GB/T 14048.1 GB/T 14048.5
Product certifications	CB Scheme CCC CE EAC
IP degree of protection	IP2X conforming to IEC 60529
Protective treatment	TH conforming to IEC 60068
Ambient air temperature for operation	-20...70 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without derating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better



Materials and Substances

[EU RoHS Directive](#)

Compliant

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins