


Product datasheet

Specifications



I max ammeter module, ComPact NSX250, 250 A rating, 3 poles

LV434851

⚠ Discontinued on: 12 May 2023

⚠ Discontinued

Main

Device short name	I max ammeter module
Product or component type	Ammeter
Device application	Metering
Range compatibility	ComPact ComPact NSX250
Poles description	3P
[In] rated current	250 A
Accuracy class	Class 4.5

Complementary

Measurement accuracy	Ammeter: +/- 6 %
----------------------	------------------

Environment

Electrical shock protection class	Class II
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK04 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.5 cm
Package 1 Width	15.5 cm
Package 1 Length	18 cm
Package 1 Weight	940 g

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins