

Product datasheet

Specifications



motor-mechanism - MT100/160 - SDE adaptor - 110..130 V AC 50/60Hz

LV429433

Price: 4,635.00 HKD

Main

Device short name	MT250
Product or component type	Motor mechanism
Device application	Automatic spring charging
Range compatibility	ComPacT NSX100 ComPacT NSX160 ComPacT NSX100 DC ComPacT NSX160 DC
Control type	Standard
[Uc] control circuit voltage	110...130 V AC 50/60 Hz
circuit breaker mounting mode	Fixed
circuit breaker frame rated current	100 A 160 A

Complementary

Control signal type	Maintained Impulse
circuit breaker response time	< 700 ms open < 80 ms closed
Maximum operating frequency	4 per minute
Maximum power consumption in VA	500 VA closing 500 VA opening
Provided equipment	SDE adaptor
Locking options description	Padlocking in OFF position 1 to 3 padlocks Ø 5 to Ø 8

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12 cm
Package 1 Width	10.5 cm
Package 1 Length	17.3 cm
Package 1 Weight	1.386 kg
Unit Type of Package 2	S04
Number of Units in Package 2	15
Package 2 Height	30 cm
Package 2 Width	40 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Length	60 cm
Package 2 Weight	21.661 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	14 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint of the manufacturing phase [A1 to A3]	9 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.3 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.9 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	3 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	A3dc0f23-906d-490a-acce-c58e25990143
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	73
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins