

Product data sheet

Specifications

SQUARE D



DRUM SWITCH 600VAC 2HP A +OPTIONS

2601AF2B

⚠ Discontinued

Main

Device Application	Manual reversing control
Device short name	A
Enclosure type	Oil resistant enclosure indoor Dustproof enclosure indoor

Complementary

Cam switch function	Reversing switch
Depth	5.58 in (141.73 mm)
Device mounting	Flush
Electrical Connection	Screw clamp terminal
Height	5.2 in (132.08 mm)
Maximum Horse Power Rating	2 hp 230 V AC, 1 phase 2 hp 115 V AC, 3 phase 1.5 hp 200/575 V AC, 1 phase
Number of poles	3
Permissible voltage	600 V AC 250 V DC
Type of operator	Ball bearing plunger Drive shaft
Width	3.38 in (85.85 mm)

Environment

NEMA Degree of Protection	NEMA 13
Product Certifications	UL Listed CSA

Ordering and shipping details

Category	21116-2601
Discount Schedule	CP1
GTIN	00785901717225
Returnability	No
Country of origin	MX

Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package weight(Lbs)	21.60 oz (612.35 g)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No