

New!

XB7 Selector Switches and Key Switches

Table 19.206: Title

Shape of head	Type of operator	Type of contact		Number and type of positions	Sold in lots of	Catalog Number
		N.O.	N.C.			
	Standard handle, black	1	—	2, maintained		10 XB7ND21
		1	1	2, maintained		10 XB7ND25
		2	—	3, maintained		10 XB7ND33
	Key (key No. 455)	1	—	2, key withdrawal in LH position		10 XB7NG21
		2	—	3, key withdrawal in center position		10 XB7NG33

NOTE: The symbol  indicates key withdrawal position(s).

New!

XB7 Mushroom Head Push Buttons

Table 19.207: Ø 40 mm Emergency Stop Trigger Action and Mechanically Latching Mushroom Head Pushbuttons

Shape of head	Type of push	Standards	Type of contact		Color	Sold in lots of	Catalog Numbers
			N.O.	N.C.			
	Turn to release	EN/IEC 60204-1, EN/ISO 13850, EN/IEC 60947-5-5, Machinery directive 2006/42/ EC and UL	—	1	Red	10	XB7NS8442
			1	1	Red	10	XB7NS8445
			—	2	Red	10	XB7NS8444
	Push-pull		—	1	Red	10	XB7NT842
			1	1	Red	10	XB7NT845
			—	2	Red	10	XB7NT844
	Key release (n° 455)		—	2	Red	10	XB7NS9444
			—	1	Red	10	XB7NS9445

Table 19.208: Circular Legends, Yellow, For Mushroom Head Push Buttons

Used for "Emergency Stop" function [108]			
Conforming to Standards	Diameter (mm)	Marking on Yellow Background	Catalog Number
EN/IEC 60204-1 and EN/ISO 13850 [108]	60	ARRET D'URGENCE	ZBY9130
		NOT-HALT	ZBY9230
		PARADA DE EMERGENCIA	ZBY9430
		ARRESTO DE EMERGENZA	ZBY9630
	90	ARRET D'URGENCE	ZBY8130
		EMERGENCY STOP	ZBY8330
		PARADA DE EMERGENCIA	ZBY8430
		ARRESTO DE EMERGENZA	ZBY8630



XB7ND2●



XB7NG33



XB7NS84●



ZBY9330

[108] For compliance with standard EN/ISO 13850, paragraph 4.4.6, the Emergency stop logo has been added.