

SIPLUS IPC 427E based on 6AG1141-5BG37-0FA0 with conformal coating, 0...+55 °C, HD graphic onboard, 4x USB V3.0 (high current), PCIe (optional), 24 V DC power supply Core i5-6442EQ; 3x Gbit Ethernet (IE/PN); DIN-rail mounting; 8 GB and NVRAM; 2x RS232/485; without PCIe; Windows 10 IoT Enterprise 2016 LTSB (64-bit) for Celeron, I3 and I5, without exchangeable mass storage;

General information	
Product type designation	IPC427E
based on	6AG1141-5BG37-0FA0
Installation type/mounting	
Mounting	DIN rail, wall mounting, portrait mounting
Design	Box PC, built-in unit
Supply voltage	
Type of supply voltage	24 V DC
Processor	
Processor type	Core i5-6442EQ (4C/4T, 1.9 (2.7) GHz, 6 MB cache)
Graphic	
Graphics controller	Intel HD graphics controller
Graphics card	Yes
Drives	
Hard disk	2.5" SATA ≥ 320 GB
SSD	Yes; ≥ 80 GB, optional ≥ 160 GB
Storage	
Type of memory	DDR4 SO-DIMM
Main memory	4 GB to 16 GB, ECC optional
Capacity of main memory, max.	16 Gbyte
Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags), max.	512 kbyte; 128 KB can be stored in the buffer time; optional
Hardware configuration	
Slots	
• Number of PCI slots	2; Optional
• Number of compact flash slots	2; CFast
Interfaces	
Number of PROFINET interfaces	1; 3 ports (incl. switch)
serial interface	Without / 2x COM (RS 232 / 485 / 422; switchable)
Video interfaces	
• Graphics interface	2x DisplayPort
Industrial Ethernet	
• Industrial Ethernet interface	
— 100 Mbps	Yes
— 1000 Mbps	Yes
Interrupts/diagnostics/status information	
LED status display	Yes
Bus diagnostics	Yes
Integrated Functions	
Monitoring functions	
• Temperature monitoring	Yes
• Monitoring function via network	Optional
Degree and class of protection	
IP (at the front)	IP20
IP (rear)	IP20
Ambient conditions	

Ambient temperature during operation			
• min. • max.	0 °C; = Tmin (incl. condensation/frost) 55 °C; = Tmax		
Altitude during operation relating to sea level			
• Installation altitude above sea level, max. • Ambient air temperature-barometric pressure-altitude	5 000 m Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)		
Relative humidity			
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation		
Resistance			
Use in stationary industrial systems			
— to biologically active substances according to EN 60721-3-3 — to chemically active substances according to EN 60721-3-3 — to mechanically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * Yes; Class 3S4 incl. sand, dust, *		
Use on ships/at sea			
— to biologically active substances according to EN 60721-3-6 — to chemically active substances according to EN 60721-3-6 — to mechanically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * Yes; Class 6S3 incl. sand, dust; *		
Remark			
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!		
Conformal coating			
• Coatings for printed circuit board assemblies acc. to EN 61086 • Protection against fouling acc. to EN 60664-3 • Military testing according to MIL-I-46058C, Amendment 7 • Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Class 2 for high reliability Yes; Type 1 protection Yes; Discoloration of coating possible during service life Yes; Conformal coating, Class A		
Operating systems			
pre-installed operating system		Windows 10 IoT Enterprise 2016 LTSP, 64bit, MUI	
Dimensions			
Width		262 mm	
Height		139.69999 mm	
Depth		55.5 mm	
Classifications			
		Version	Classification
eClass		14	19-20-01-02
eClass		12	19-20-01-02
eClass		9.1	19-20-01-02
eClass		9	19-20-01-02
eClass		8	19-20-01-02
eClass		7.1	19-20-01-02
eClass		6	19-20-01-02
ETIM		10	EC001413
ETIM		9	EC001413
ETIM		8	EC001413
ETIM		7	EC001413
IDEA		4	6606
UNSPSC		15	43-21-15-06
Approvals / Certificates			

General Product Approval

[Manufacturer Declaration](#)



[Declaration of Conformity](#)

[China RoHS](#)



[China RoHS](#)

General Product Approval	Maritime application
--------------------------	----------------------



last modified:

4/17/2026