

# Product datasheet

Specifications



## contactor CT - 2 poles - 2 NO - 25 A - 220..240 V AC

16145

⚠ Discontinued on: 6 May 2019

⚠ Discontinued

## Main

Product or component type	Contactor
Device short name	CT
Device application	Control circuit
Poles	2P
[Ie] rated operational current	25 A AC-7A
Pole contact composition	2 NO
Network type	AC
Control type	Remote control
[Uc] control circuit voltage	220/240 V AC 60 Hz

## Complementary

Network frequency	60 Hz
[Ue] rated operational voltage	250 V AC 60 Hz
Maximum power	3 W at 250 V AC
Control signal type	Maintained
Local signalling	Color indicator
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	60 mm
Colour	Grey
Mechanical durability	1000000 cycles
Electrical durability	100000 cycles IEC/EN 61095 25 A 60 Hz AC-7A 30000 cycles EN/IEC 60947-4-1 60 Hz AC-3
Connections - terminals	Power circuit: tunnel type terminals2 cable(s) 2.5 mm <sup>2</sup> flexible Power circuit: tunnel type terminals1 cable(s) 6 mm <sup>2</sup> rigid Control circuit: tunnel type terminals2 cable(s) 2.5 mm <sup>2</sup> flexible Control circuit: tunnel type terminals2 cable(s) 1.5 mm <sup>2</sup> rigid
Product compatibility	Mixed control: impulse/latched Auxiliary contact Interference filter Time delay

---

Compatibility code	CT
--------------------	----

## Environment

---

Standards	IEC/EN 61095
-----------	--------------

---

Product certifications	CCC VDE IMQ EAC CEBEC
------------------------	-----------------------------------

---

Noise level	30 dB
-------------	-------

---

IP degree of protection	IP20
-------------------------	------

---

Pollution degree	2
------------------	---

---

Tropicalisation	2 conforming to EN 60947-4-1 2 conforming to EN 61095 2 conforming to IEC 1095
-----------------	--

---

Relative humidity	95 % at 55 °C
-------------------	---------------

---

Operating altitude	2000 m
--------------------	--------

---

Ambient air temperature for operation	-5...60 °C
---------------------------------------	------------

---

Ambient air temperature for storage	-40...60 °C
-------------------------------------	-------------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	6.5 cm
------------------	--------

---

Package 1 Width	1.8 cm
-----------------	--------

---

Package 1 Length	8.5 cm
------------------	--------

---

Package 1 Weight	0.118 kg
------------------	----------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Longer



### Lifetime extension

[Repair](#)

[No](#)

## Use Again



### Repack and remanufacture

[WEEE Label](#)



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins