


Product datasheet

Specifications



CONNECTIONS 160A 4P LINERGY BW/DEVICE 160A W165

04147

⚠ Discontinued on: 29 Nov 2021

⚠ Discontinued

Main

Range	Linergy
Range of product	Linergy
Product or component type	One-piece connection
Product name	Linergy BW
product name	Prisma Prisma P enclosure Prisma Prisma G enclosure Linergy Linergy BW busbar
Provided equipment	With connection
Standards	IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma
Product certifications	ASEFA

Complementary

Cubicle-device connection	Linergy BW busbar
Poles description	4P
installation description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Pack enclosure - width 550 mm
Installed device	Multi9: NG125 ComPact: NG160 ComPact: INS160 Multi9: C120 Acti 9: iC120
[Ie] rated operational current	160 A
[In] rated current	160 A
Length	165 mm
Net weight	0.48 kg
Quantity per set	Set of 1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5 cm
Package 1 Width	10 cm

Package 1 Length	20 cm
------------------	-------

Package 1 Weight	480 g
------------------	-------

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant](#)

Halogen-free status

Halogen free plastic parts product

PVC free

Yes

Silicone-free

Yes

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Take-back

Nej