


Product datasheet

Specifications

Motors



AC servo motor BDH - 1.08 N.m -
8000 rpm - untapped shaft - without
brake - IP54

BDH0583F02A2B

EAN Code: 3389118191068

! Discontinued

Main

Product or component type	AC servo motors
Component name	BDH
Continuous stall torque	1.08 N.m for LXM15LD21M3 single phase 1.18 N.m for LXM15LD21M3 3 phases
Peak stall torque	2.62 N.m for LXM15LD21M3 at 230 V single phase 3.52 N.m for LXM15LD21M3 at 230 V 3 phases
Nominal output power	770 W for LXM15LD21M3 at 230 V 3 phases 770 W for LXM15LD21M3 at 230 V single phase
Nominal torque	0.92 N.m for LXM15LD21M3 at 230 V 3 phases 0.92 N.m for LXM15LD21M3 at 230 V single phase
Nominal speed	8000 rpm for LXM15LD21M3 at 230 V 3 phases 8000 rpm for LXM15LD21M3 at 230 V single phase
Maximum mechanical speed	8000 rpm
Product compatibility	LXM15LD21M3 at 230 V 3 phases LXM15LD21M3 at 230 V single phase
Shaft end	Untapped
IP degree of protection	IP54
Encoder type	Absolute multiturn SinCos Hiperface
Speed feedback resolution	1048576 points/turn x 4096 turns
Holding brake	Without
Mounting support	NEMA flange
Electrical connection	Rotatable right-angled connectors
Number of poles	6

Complementary

Range compatibility	Lexium 15
Maximum current Irms	12.16 A
Torque constant	0.27 N.m/A at 120 °C
Back emf constant	17.6 V/krpm at 120 °C
Stator resistance	2.23 Ohm at 20 °C
Stator inductance	4.68 mH at 20 °C
Stator electrical time constant	at 20 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Maximum radial force Fr	127 N at 8000 rpm
	128 N at 7000 rpm
	130 N at 6000 rpm
	132 N at 5000 rpm
	133 N at 4000 rpm
	135 N at 3000 rpm
	137 N at 2000 rpm
	138 N at 1000 rpm
Maximum axial force Fa	0.3 x Fr
Net weight	1.38 kg



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No