

Product datasheet

Specifications



P115 self power - In 5A - Ion 1A 0.01-2Ion - no Vx

REL10119

⚠ Discontinued on: 30 Jun 2023

⚠ Discontinued

Main

Range of product	MiCOM P11x
Device short name	P115
Relay application	Feeder
Input output max capacity	2 inputs + 4 outputs
Communication port protocol	Modbus RTU IEC 60870-5-103

Complementary

Type of measurement	Current
auxiliary supply	60...240 V AC 60...250 V DC
Display type	LCD display: 2 lines of 16 characters ASCII (European characters) and 9 key
earth current inputs	5 A 0.2...40 In
Communication port support	RS485 USB

Environment

Device mounting	Flush
Mounting mode	Flush-mounted

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21.8 cm
Package 1 Width	15.8 cm
Package 1 Length	25.6 cm
Package 1 Weight	2.14 kg

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No