

PRODUCT-DETAILS

ACS580-01-073A-4

LV AC general purpose wall-mounted drive, IEC:
Pn 37 kW, 73 A, 400 V, 480 V (ACS580-01-073A-4)



General Information

Global Commercial Alias	ACS580-01-073A-4
Product ID	3AUA0000080499
ABB Type Designation	ACS580-01-073A-4
EAN	6438177305552
Catalog Description	LV AC general purpose wall-mounted drive, IEC: Pn 37 kW, 73 A, 400 V, 480 V (ACS580-01-073A-4)
Long Description	<p>The ACS580-01 is plug-in ready to control your compressors, conveyors, pumps, extruders, centrifuges, mixers, fans and many other variable and constant torque applications, in a variety of light industries, including food and beverage, plastic, textile, material handling, and agriculture.</p> <p>All essential features are built-in as standard, simplifying drive selection, and making additional hardware unnecessary. Versatile and straightforward settings menu and assistants enable fast setup, commissioning, use and maintenance, while rugged and robust design makes it a good fit for various environments. With the ACS580 drives you can easily take full control of your processes to comprehensively manage your plant. The wall-mounted ACS580-01 comes in IP21 enclosure as standard. Also, IP55 and flange mounting units are available.</p>

Ordering

Country of Origin	Finland (FI)
Customs Tariff Number	85044086
HS Code	850440-- Electrical transformers, static converters (for example, rectifiers) and inductors.- Static converters
Invoice Description	ACS580-01-073A-4 PN: 37 kW, IN: 73 A

Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Container Information

Gross Volume	33.181 dm ³
--------------	------------------------

Dimensions

Product Net Weight	20 kg 44.092 lb
Product Net Depth / Length	257.00 mm 10.12 in
Product Net Height	636 mm 25.04 in
Product Net Width	203.00 mm 7.99 in
Package Level 1 Depth / Length	760.00 mm 31 in
Package Level 1 Height	428.00 mm 14 in
Package Level 1 Width	298.00 mm 11 in
Package Level 1 Units	1 carton

Technical

Number of Phases	3
Degree of Protection	IP21
Enclosure Type NEMA	Type1
Altitude	1000 m
Sound dB (A)	95
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R4
Input Voltage (U_{in})	380 ... 480 V
Mounting Type	Wall-mounted
Communication Protocol	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes	Control unit PC connection
Analog Inputs	2

Analog Outputs	2
Number of Digital In/Outputs	6 / 3
Output Current, Heavy-Duty Use (I_{HD})	61 A
Output Current, Light-Overload Use (I_{LD})	68 A
Output Current, Normal Use (I_n)	73 A
Output Power, Heavy-Duty Use (P_{HD})	30.0 kW
Output Power, Light-Overload Use (P_{LD})	37 kW
Output Power, Normal Use (P_n)	37 kW
Apparent Power Output	51 kV·A
Efficiency Level	IE2
Standby Loss	19 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	295 W	90.1 %	0.6 %
0/50 %	392 W	93.0 %	0.8 %
0/100 %	726 W	93.4 %	1.4 %
50/25 %	324 W	94.5 %	0.6 %
50/50 %	454 W	96.0 %	0.9 %
50/100 %	866 W	96.1 %	1.7 %
90/50 %	527 W	97.4 %	1.0 %
90/100 %	1120 W	97.2 %	2.2 %

Temperature Rating	Maximum 40 °C Minimum -15 °C
--------------------	---------------------------------

Classifications

ETIM 8	EC001857 - Frequency converter =< 1 kV
ETIM 9	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

Environmental

SCIP	596c7575-1ed1-48e9-be9a-d8fdd900606b Finland (FI)
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Additional Information

Product Main Type	ACS580-01
Product Name	Frequency converter

Categories

Drives → Low Voltage AC Drives → General Purpose Drives → ACS580-01 - Wall-mounted drive

