



SIMATIC ET 200SP HA, holder module IM redundant, support for holding two redundant interface modules of the SIMATIC ET 200SP HA, including server module

General information	
Product type designation	Carrier module IM redundant
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; Asset data
Supply voltage	
Rated value (DC)	24 V
Hardware configuration	
Slots	
<ul style="list-style-type: none"> <li>Number of slots</li> </ul>	2
Potential separation	
between backplane bus and supply voltage	Yes
Isolation	
Isolation tested with	1 500 V DC/1 min, type test
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>horizontal installation, min.</li> <li>horizontal installation, max.</li> <li>vertical installation, min.</li> <li>vertical installation, max.</li> </ul>	-40 °C 70 °C -40 °C 60 °C
Dimensions	
Width	100 mm
Height	141 mm
Depth	29 mm; measured without power plug
Weights	
Weight, approx.	142 g; measured without power plug

Classifications			
		Version	Classification
	eClass	14	27-24-26-07
	eClass	12	27-24-26-07
	eClass	9.1	27-24-26-07
	eClass	9	27-24-26-07
	eClass	8	27-24-26-07
	eClass	7.1	27-24-26-07
	eClass	6	27-24-26-07
	ETIM	10	EC001603
	ETIM	9	EC001603
	ETIM	8	EC001603

## Approvals / Certificates

## General Product Approval



## For use in hazardous locations

[Declaration of Con-  
formity](#)[Miscellaneous](#)

last modified:

10/23/2025