



Main

Range of product	Modicon Premium Automation platform
Product or component type	Double-format PL7 processor
Software designation	PL7 Junior/Pro

Complementary

Number of racks	16 4/6/8 slots 8 12 slots
Number of slots	128 64 96
Discrete I/O processor capacity	2040 I/O
Analogue I/O processor capacity	256 I/O
Number of application specific channel	<= 64
Number of process control channel	<= 20 up to 60 simple loops
Integrated connection type	Fipio manager (127 agents) SUB-D 9 Non isolated serial link 2 female mini DIN 19.2/115 kbit/s
Communication module processor capacity	2 fieldbus modules (1 if CANopen used) 8 AS-Interface bus modules 1 CANopen 4 network module
Memory description	Internal RAM (with PCMCIA card) 176 Kwords data Internal RAM (without PCMCIA card) 96 Kwords program and data PCMCIA card 2048 Kwords additional data storage PCMCIA card 992 Kwords program
Maximum size of object areas	30.5 %MWi internal words located internal data 32 %KWi constant words located internal data 32768 %Mi located internal bits
Application structure	1 fast task 1 master task 64 event tasks
Execution time per instruction	0.06 µs Boolean with PCMCIA card 0.06 µs Boolean without PCMCIA card 0.08 µs word or fixed-point arithmetic with PCMCIA card 0.08 µs word or fixed-point arithmetic without PCMCIA card 1.7 µs floating points with PCMCIA card 1.7 µs floating points without PCMCIA card
Number of instructions per ms	13.82 Kinst/ms 100 % Boolean with PCMCIA card 13.82 Kinst/ms 100 % Boolean without PCMCIA card 8.8 Kinst/ms 65 % Boolean + 35 % fixed arithmetic with PCMCIA card 8.8 Kinst/ms 65 % Boolean + 35 % fixed arithmetic without PCMCIA card
System overhead	0.22 ms fast task 1.15 ms master task
Marking	CE
Local signalling	1 LED green processor running (RUN) 1 LED red activity on Fipio bus (FIP) 1 LED red I/O module or configuration fault (I/O) 1 LED red processor or system fault (ERR) 1 LED yellow activity on the terminal port (TER)
Current consumption	1080 mA 5 V DC
Module format	Double
Product weight	1.23 lb(US) (0.56 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

standards	73/23/EEC 89/336/EEC 92/31/EEC 93/68/EEC CSA C22.2 No 142 IEC 61131-2 UL 508 CSA C22.2 No 213 Class I Division 2 Group A CSA C22.2 No 213 Class I Division 2 Group B CSA C22.2 No 213 Class I Division 2 Group C CSA C22.2 No 213 Class I Division 2 Group D
product certifications	ABS BV DNV GL LR RINA RMRS
ambient air temperature for operation	32...140 °F (0...60 °C)
ambient air temperature for storage	-13...158 °F (-25...70 °C)
relative humidity	10...95 % without condensation for operation 5...95 % without condensation for storage
operating altitude	0...6561.68 ft (0...2000 m)
protective treatment	TC
IP degree of protection	IP20
pollution degree	2

Offer Sustainability


Not Green Premium product	Not Green Premium product
Compliant - since 0935 - Schneider Electric declaration of conformity	Compliant - since 0935 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------

Standard and Extendable Racks for Modules Mounting

Dimensions of Modules and Racks



(1) With screw terminal block modules.

(2) Maximum depth for all types of modules and their associated connectors.