

Product data sheet

Specifications



Sercos connector distributor & 24 V- Out on Lexium 62 distribution box ILM62DB

VW3E6047

**Product availability: Non-Stock - Not normally stocked in
distribution facility**

Main

Range of Product	PacDrive 3
Accessory / separate part category	Connection accessory
Product or Component Type	Connector adaptor
Range Compatibility	Lexium 62 ILM
Product compatibility	LXM 62 ILM integrated drive

Complementary

Type of cooling	Natural convection
Overvoltage category	Class 3 conforming to IEC 61800-5-1
Width	4.7 in (120 mm)
Height	3.1 in (80 mm)
Depth	1.0 in (25 mm)
Net Weight	1.59 lb(US) (0.72 kg)

Environment

IP Degree of Protection	IP65
Pollution degree	2 EN/IEC 60721-3-3

Ordering and shipping details

Category	US1PC5218351
Discount Schedule	PC52
GTIN	3606485402086
Returnability	Yes
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.0 in (2.5 cm)
Package 1 Width	4.7 in (12.0 cm)
Package 1 Length	3.1 in (8.0 cm)
Package weight(Lbs)	25.4 oz (720.0 g)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No