

***** Replacement part ***** SIMATIC S7-400, Interface module Send IM 463-2 for distributed coupling to SIMATIC S5 expansion devices via IM 314, up to 600 m

Input current	
from backplane bus 5 V DC, max.	1 320 mA
Power loss	
Power loss, max.	6 600 mW
Hardware configuration	
Cable length between first and last interface module, max.	600 m
Dimensions	
Width	25 mm
Height	290 mm
Depth	217 mm
Weights	
Weight, approx.	360 g
Classifications	

	Version	Classification
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates
General Product Approval

[China RoHS](#)

EMV

For use in hazardous locations



EM



For use in hazardous locations	Maritime application
--------------------------------	----------------------

[Type Examination Certificate](#)



Maritime application



[CCS \(China Classification Society\)](#)

last modified:

7/21/2025 