

SIMATIC S7 synchronization module V8 XTR for patch cable up to 10 m extended design for the process automation



Input current	
Current consumption, max.	240 mA
Power loss	
Power loss, typ.	0.7 W
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	70 °C
Dimensions	
Width	11 mm
Height	14 mm
Depth	58 mm
Weights	
Weight, approx.	18 g

Classifications			
		Version	Classification
	eClass	14	27-24-22-08
	eClass	12	27-24-22-08
	eClass	9.1	27-24-22-08
	eClass	9	27-24-22-08
	eClass	8	27-24-22-08
	eClass	7.1	27-24-22-08
	eClass	6	27-24-22-08
	ETIM	10	EC001423
	ETIM	9	EC001423
	ETIM	8	EC001423
	ETIM	7	EC001423
	IDEA	4	3564
	UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



General Product Approval

For use in hazardous locations

[Miscellaneous](#)

[China RoHS](#)



[FM](#)



[Type Examination Certificate](#)

For use in hazardous locations

Maritime application



Maritime application

Environment

[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)



last modified:

4/30/2025