

# Product datasheet

Specifications



## Bistable contactor CR1-F - 4P - AC-1 440V 500 A - coil 415 V

CR1F4004N7

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

### Main

Range	TeSys
Product name	TeSys F
Product or component type	Magnetic latching contactor
Device short name	CR1F
Device application	Control
Contactor application	Motor control Resistive load
Utilisation category	AC-3 AC-1 AC-4
Poles description	4P
power pole contact composition	4 NO
[Ue] rated operational voltage	1000 V AC 25...200 Hz
[Ie] rated operational current	400 A (at <40 °C) at <= 440 V AC AC-3 500 A (at <40 °C) at <= 440 V AC AC-1 370 A (at <40 °C) at <= 440 V AC AC-4
Motor power kW	185 kW at 1000 V AC 50/60 Hz 280 kW at 690 V AC 50/60 Hz 257 kW at 500...660 V AC 50/60 Hz 250 kW at 440 V AC 50/60 Hz 220 kW at 415 V AC 50/60 Hz 200 kW at 380...400 V AC 50/60 Hz 110 kW at 220...230 V AC 50/60 Hz
motor power HP (UL / CSA)	300 hp at 575...600 V AC 50/60 Hz for 3 phases motors 250 hp at 460...480 V AC 50/60 Hz for 3 phases motors 125 hp at 220...240 V AC 50/60 Hz for 3 phases motors 100 hp at 200...208 V AC 50/60 Hz for 3 phases motors
[Uc] control circuit voltage	415 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	500 A (at 40 °C) for power circuit
Irms rated making capacity	4500 A for power circuit
Rated breaking capacity	4000 A at 220...440 V for power circuit 3500 A at 500 V for power circuit 1200 A at 1000 V for power circuit 3000 A at 660/690 V for power circuit

<b>[Icw] rated short-time withstand current</b>	3600 A 40 °C - 1 s 3600 A 40 °C - 5 s 3600 A 40 °C - 10 s 2400 A 40 °C - 30 s 1700 A 40 °C - 1 min 1200 A 40 °C - 3 min 1000 A 40 °C - 10 min
<b>Associated fuse rating</b>	400 A aM at <= 440 V for power circuit 500 A BS88 at <= 440 V for power circuit 500 A gG at <= 440 V for power circuit
<b>Average impedance</b>	0.28 mOhm - Ith 500 A 50 Hz
<b>[Ui] rated insulation voltage</b>	1000 V conforming to IEC 60158-1 1000 V conforming to IEC 60947-4 1000 V conforming to BS 775 1500 V conforming to VDE 0110 group C
<b>Power dissipation per pole</b>	45 W AC-3 70 W AC-1
<b>Mounting support</b>	Notched AM1-EC rail
<b>Standards</b>	NF C 63-110 BS 5424 IEC 60947-4 VDE 0660 JEM 1038
<b>Product certifications</b>	LROS (Lloyds register of shipping) Veritas GL USSR UL BV CSA ASE RINA
<b>Connections - terminals</b>	Lugs-ring terminals 2 cable(s) 150 mm <sup>2</sup> Bars 2 cable(s) - busbar cross section: 30 x 5 mm
<b>Tightening torque</b>	35 N.m
<b>Operating time</b>	40...75 ms latching 50...100 ms unlatching
<b>Mechanical durability</b>	1 Mcycles
<b>Maximum operating rate</b>	120 cyc/h 40 °C

## Complementary

<b>Control circuit voltage limits</b>	Latching: 0.85...1.1 Uc Unlatching: 0.85...1.1 Uc
<b>average consumption</b>	1600 VA AC 50...400 Hz latching 16 VA AC 50...400 Hz unlatching 1600 VA DC latching 16 VA DC unlatching

## Environment

<b>IP degree of protection</b>	IP20 front face conforming to IEC 60529
<b>Protective treatment</b>	TH
<b>Ambient air temperature for operation</b>	-15...70 °C
<b>Ambient air temperature for storage</b>	-60...80 °C
<b>Operating altitude</b>	3000 m without derating
<b>Height</b>	206 mm
<b>Width</b>	261 mm

---

<b>Depth</b>	219 mm
--------------	--------

---

<b>Net weight</b>	10.2 kg
-------------------	---------

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	25 cm
-------------------------	-------

---

<b>Package 1 Width</b>	24 cm
------------------------	-------

---

<b>Package 1 Length</b>	31 cm
-------------------------	-------

---

<b>Package 1 Weight</b>	10.91 kg
-------------------------	----------

---

## Contractual warranty

---

<b>Warranty (in months)</b>	18
-----------------------------	----

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

[EU RoHS Directive](#)

Compliant

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins