

surge suppressor, suppression diode with LED, 150-250 V DC, for contactors 3RT2.1 and auxiliary contactors 3RH2, multi-unit packaging, pack = 10 units

product brand name	SIRIUS
product category	Surge suppressor
product designation	Interference suppression diode with LED
suitability for use	for 3RT2.1 contactors and 3RH2 auxiliary contactors

General technical data

certificate of suitability	CE / UL / CSA
size of contactor	S00
Substance Prohibitance (day/month/year)	10/01/2009
SVHC substance name	Lead CAS-No. 7439-92-1
Net Weight	0.005 kg
type of voltage of the control supply voltage	DC
control supply voltage at DC rated value	150 ... 250 V
design of the surge suppressor	diode

Ambient conditions

ambient temperature	
<ul style="list-style-type: none"> during operation 	-25 ... +60 °C
<ul style="list-style-type: none"> during storage 	-40 ... +80 °C

Installation/ mounting/ dimensions

mounting position	any
fastening method	clip-on
height	46 mm
width	28 mm
depth	9 mm

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2916-1LP00-Z X90>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2916-1LP00-Z X90>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2916-1LP00-Z X90>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2916-1LP00-Z X90&lang=en



