

# Product datasheet

Specifications

rear connection upside vertical  
mounting - 3 poles - for NT 08..20  
drawout



34111

⚠ Discontinued on: May 19, 2023

⚠ Discontinued

## Main

Range of product	MasterPact NT UL 489
Product or component type	Rear connection
Accessory / separate part category	Connection accessory
Range compatibility	Masterpact MasterPact NT UL 489 MasterPact NT08 circuit breaker Masterpact MasterPact NT UL 489 MasterPact NT10 circuit breaker Masterpact MasterPact NT UL 489 MasterPact NT12 circuit breaker
Poles description	3P
Mounting mode	Drawout
[In] rated current	800...2000 A

## Complementary

Location of connection	Rear
Localisation on device	Upside
Connection position	Vertical
Connection pitch	70 mm

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2 cm
Package 1 Width	8 cm
Package 1 Length	20 cm
Package 1 Weight	1.7 kg

## Contractual warranty

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No