



Main

Range	TeSys
Product or component type	Undervoltage trip
Device short name	GV7AS
Range compatibility	TeSys TeSys GV7

Complementary

[Uc] control circuit voltage	200...240 V AC 50/60 Hz
Control circuit voltage limits	0.85...1.1 Un
[Ui] rated insulation voltage	600 V AC conforming to UL 508 control circuit 690 V AC conforming to IEC 60947-1 control circuit 600 V AC conforming to CSA C22.2 No 14 control circuit
Threshold tripping voltage	0.35...0.7 Ue
Inrush power in VA	< 10 VA AC network
Hold-in power consumption in VA	< 5 VA AC network
Operating time	< 50 ms conforming to IEC 60947-1
On-load factor	100 %
Connections - terminals	Control circuit: screw clamp terminals 1 cable 0 in ² (1 mm ²) - cable stiffness: flexible - with cable end Control circuit: screw clamp terminals 1 cable 0 in ² (1.5 mm ²) - cable stiffness: flexible - without cable end Control circuit: screw clamp terminals 1 cable 0 in ² (1.5 mm ²) - cable stiffness: solid
Tightening torque	Control circuit : 1.2 N.m - on screw clamp terminals
Product weight	0.23 lb(US) (0.105 kg)
Quantity per set	Set of 10

Environment

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0744 - Schneider Electric declaration of conformity	Compliant - since 0744 - Schneider Electric declaration of conformity
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer.	Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------