



Main

Range	PowerLogic
Product or Component Type	I/O module
Device Application	Optional expansion module
Range compatibility	PowerLogic (PowerLogic PM8000) PowerLogic (PowerLogic ION7400) PowerLogic (PowerLogic ION9000)

Complementary

Number of outputs	2 analog, 0-20 mA or 4-20 mA 0...10 V
Number of inputs	4 analog 0...20 mA/4...20 mA 0...30 V
Width	0.87 in (22 mm)
Depth	3.56 in (90.5 mm)
Height	3.56 in (90.5 mm)
Net Weight	4.94 oz (140 g)

Environment

Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
IP degree of protection	IP30 IEC 60529

Ordering and shipping details

Category	09782-POWERLOGIC PM8000 ACCESSORIES
Discount Schedule	PL1
GTIN	3606480702006
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.36 in (6 cm)
Package 1 Width	3.94 in (10 cm)
Package 1 Length	4.72 in (12 cm)
Package 1 Weight	7.87 oz (223 g)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.