

# Product datasheet

Specifications



## Circuit breaker MasterPact NW40EPDC-D, 4000A, 1100VDC, 65kA/1100VDC (Icu), 3 poles, drawout, without control unit

46924

EAN Code: 3606481947567

### Main

Range	MasterPacT
Product name	MasterPact NW DC
Product or component type	Circuit breaker
Device application	Marine application
Poles description	3P
Control unit	Without control unit
[In] rated current	4000 A at 40 °C
[Ue] rated operational voltage	1100 V DC
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Selectivity category	Category B
Control type	Push-button
Mounting mode	Drawout

### Complementary

[Icu] rated ultimate short-circuit breaking capacity	65 kA Icu at 1100 V DC L/R = 15 ms
[Ics] rated service breaking capacity	65 kA at 1100 V DC (L/R = 15 ms)
[Icw] rated short-time withstand current	65 kA 1 s
[Icm] rated short-circuit making capacity	65 kA L/R = 15 ms 1100 V DC
Sensor rating	4000 A
[Ui] rated insulation voltage	1250 V DC
[Uimp] rated impulse withstand voltage	12 kV
Power dissipation in W	4000 W
Maximum breaking time	30...75 ms
Maximum closing response time	70 ms
Mounting support	Backplate Rails
Upside connection	Rear
Downside connection	Rear
Connection pitch	150 mm
Mechanical durability	10000 cycles without maintenance conforming to IEC 60947-2 20000 cycles with maintenance conforming to IEC 60947-2

<b>Electrical durability</b>	2000 cycles 1100 V DC without maintenance conforming to IEC 60947-2
<b>Height</b>	439 mm
<b>Width</b>	441 mm
<b>Depth</b>	594 mm
<b>Net weight</b>	90...116 kg
<b>Standards</b>	IEC 60947-2
<b>Product certifications</b>	ASEFA ASTA

## Environment

<b>Pollution degree</b>	3 conforming to IEC 60664-1
<b>Ambient air temperature for operation</b>	-25...70 °C
<b>Ambient air temperature for storage</b>	-40...85 °C
<b>Operating altitude</b>	0...2000 m without derating 2000 m...5000 m with derating

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	70.0 cm
<b>Package 1 Width</b>	60.0 cm
<b>Package 1 Length</b>	80.0 cm
<b>Package 1 Weight</b>	136.0 kg

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	5 041 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	503 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	12 kg CO2 eq.
Carbon footprint of the installation phase [A5]	17 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	4 327 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	181 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards
SCIP Number	A5b47f2e-24bf-47cc-87fb-b0762b13883c
Silicone-free	No

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	69
End of life manual availability	<a href="#">End of Life Information</a>
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins