

Product datasheet

Specifications



Mains supply reactance - 160A 400/500 Vac

VW3A68501

⚠ End-of-service on: Nov 24, 2021 AD

⚠ Discontinued

Main

Range of product	Altivar
Product or component type	Line choke
number of phases	3 phases
Range compatibility	Altivar 68
Device application	Reduction of current harmonics
Value of inductance	0.22 mH
[In] rated current	160 A
Saturation current	305 A
Thermal losses	220 W
Electrical connection	Terminal 6 mm ² / AWG 8, 0.8...1 N.m

Complementary

power supply frequency	50...60 Hz
Max current	1.65 x nominal current (duration = 60 s)
Maximum voltage drop at rated load	5 %
Electrical insulation class	Class F
Minimum clearance distance	5.5 mm IEC 60664
Leakage distance	11.5 mm conforming to IEC 60664
Width	280 mm
Height	305 mm
Depth	210 mm

Environment

Standards	VDE 0160 level 1 EN 50178 IEC 60076 (with HD398)
IP degree of protection	Choke: IP00 Terminals: IP20
Environmental characteristic	3B1 conforming to IEC 721-3-3 3C2 conforming to IEC 721-3-3 3S1 conforming to IEC 721-3-3
Pollution degree	2 conforming to EN 50178
Vibration resistance	1 gn (f= 13...200 Hz) conforming to IEC 60068-2-6 1.5 mm peak to peak (f= 3...13 Hz) conforming to IEC 60068-2-6

Shock resistance	15 gn for 11 ms conforming to IEC 60068-2-27
Relative humidity	0...95 %
Ambient air temperature for operation	45...55 °C (with current derating of 2 % per °C) 0...45 °C (without current derating)
Ambient air temperature for storage	-25...70 °C
Operating altitude	<= 1000 m without current derating 1000...3000 m with current derating 1 % per 100 m

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No