

Product data sheet

Specifications



Circuit breaker, MasterPacT MTZ3, ANSI, max 5000A rated, 3 pole, drawout mount, L1 breaking cap, 635VAC, w/o Micrologic trip unit, w/ ArcBlok

LV839317

Main

Product name	MasterPact MTZ1
Device short name	MTZ3 50 L1
Product or Component Type	Circuit breaker
Device Application	Protection
Poles description	3P
Network type	AC
Network Frequency	50/60 Hz
Breaking capacity code	L1

Complementary

Control Type	Push-button
Mounting Mode	Fixed
Mounting Support	Base plate Rails
Line Rated Current	5000 A 104 °F (40 °C)
Circuit breaker CT rating	5000 A
performance level	200 kA Icu 254 V AC 60 Hz ANSI C37.50 200 kA Icu 508 V AC 60 Hz ANSI C37.50 130 kA Icu 635 V AC 60 Hz ANSI C37.50 200 kA Icu 254 V AC 50 Hz ANSI C37.50 150 kA Icu 508 V AC 50 Hz ANSI C37.50 100 kA Icu 635 V AC 50 Hz ANSI C37.50
Mechanical durability	10000 cycles ANSI C37.50
Electrical durability	2800 cycles ANSI C37.50
Connection pitch	9.06 in (230 mm)
[Icw] rated short-time withstand current	100 kA 0.5 s ANSI C37.50
Integral instant protection	243...297 kA
Rated breaking and making capacity	90 kA
Maximum breaking time	9 ms
Maximum closing response time	70 ms
Height	18.8 in (478.1 mm)
Width	31.07 in (789.1 mm)
Depth	16.8 in (426.8 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

GTIN	3606489517618
------	---------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No