

# Product datasheet

Specifications



## contactor coil - LX1F - 280 V AC - 50/60 Hz

LX1FL280

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

### Main

|                              |                              |
|------------------------------|------------------------------|
| Range                        | TeSys                        |
| Product or component type    | Contactor coil               |
| Device short name            | LX1FL                        |
| Range compatibility          | TeSys TeSys F LC1F contactor |
| Control circuit type         | AC at 50/60 Hz               |
| [Uc] control circuit voltage | 280 V AC 50/60 Hz            |
| Mechanical durability        | 5 Mcycles                    |
| Maximum operating rate       | 1200 cyc/h 55 °C             |

### Complementary

|                 |                                    |
|-----------------|------------------------------------|
| Coil technology | Without built-in suppressor module |
|-----------------|------------------------------------|

### Packing Units

|                              |     |
|------------------------------|-----|
| Unit Type of Package 1       | PCE |
| Number of Units in Package 1 | 1   |

### Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained](#) >

[How we assess product sustainability](#) >



### Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Longer



### Lifetime extension

Repair

No