

Auxiliaries and accessories



Comb busbars for C60BP

www.se.com



These comb busbars are aimed to be used only with C60BP circuit breakers.

They perform distribution and subdistribution of the electric power supply and allow rapid assembly and disassembly of equipment.

Comb busbars	
Connection accessories	Comb busbars
Function	- The comb busbars make it easier to install C60BP UL 489 circuit breakers - They must not be cut
Use	Power supply by insulated connector
Standard comb busbars	
	 
Number of poles	1P 2P 3P
Catalog numbers	M9XUP106 M9XUP112 M9XUP206 M9XUP212 M9XUP306 M9XUP312
Number of 18 mm (0.71 in) mod.	6 12 6 12 6 12
Set of	1 1 1
Cuttable comb busbars	
	  
	 
	With spare spaces of 9 mm (0.35 in) for 9 mm (0.35 in) electrical auxiliary
Number of poles	1P 2P 3P 1P+Aux 3P+Aux
Catalog numbers	M9XCP157 M9XCP256 M9XCP357 M9XCA137 M9XCA348
Number of 18 mm (0.71 in) mod.	57 56 57 37 48
Set of	1 1 1 1 1
Technical specifications	
Acceptable current at 40°C (104 °F) (Ie)	Standard comb busbars: 115 A Cuttable comb busbars: 80 A
Resistance to short-circuit currents	Compatible with the breaking capacity of Schneider Electric modular circuit breakers
Voltage rating (Ue)	480Y/277 V
Insulation voltage (Ui)	1000 V AC
Pollution degree	3
Fire resistance	Self-extinguishability 960°C (1760 °F) 30 secondes
Colour	RAL 9001
Standards	UL489 and UL508