




---

 PRODUCT-DETAILS

## ACS180-04N-07A2-4

LV AC machinery drive module, IEC: Pn 3 kW, 7.2 A, 400 V, UL: Pld 3 Hp, 6.0 A, 460 V (ACS180-04N-07A2-4)




---

**General Information**

Global Commercial Alias	ACS180-04N-07A2-4
Product ID	3AXD50000716548
ABB Type Designation	ACS180-04N-07A2-4
EAN	6438177648994

Catalog Description	LV AC machinery drive module, IEC: Pn 3 kW, 7.2 A, 400 V, UL: Pld 3 Hp, 6.0 A, 460 V (ACS180-04N-07A2-4)
---------------------	--

Long Description	The ACS180 is a compact, robust, and adaptable variable speed drive (VSD) for applications such as pumps, fans, compressors, conveyors, winders and mixers. This easy-to-use compact VSD offers excellent performance and quality at superior value with all essential machinery application features embedded. And as a member of ABB's all-compatible drives portfolio, it shares the same architecture and user interfaces for ease of use.
------------------	--

---

**Ordering**

Customs Tariff Number	85044085
HS Code	850440-- Electrical transformers, static converters (for example, rectifiers) and inductors.- Static converters
Invoice Description	ACS180-04N-07A2-4 PN: 3.0 kW, IN: 7.2 A

Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

## Dimensions

Product Net Weight	1.24 kg 2.734 lb
Product Net Depth / Length	143 mm 5.630 in
Product Net Height	220 mm 8.661 in
Product Net Width	70 mm 2.756 in
Package Level 1 Depth / Length	225 mm 8.858 in
Package Level 1 Height	115 mm 4.528 in
Package Level 1 Width	220 mm 8.661 in
Package Level 1 Units	1 carton

## Technical

Number of Phases	3
Degree of Protection	IP20
Enclosure Type NEMA	Open Type
Altitude	2000 m 5 ... 95
Power Factor	0.98
Sound dB (A)	50.9 dB(A)
Multiple Battery Information	No battery / cell included
Frequency (f)	47 ... 63 Hz
Frame Size	R1
Input Voltage (U <sub>in</sub> )	380 ... 480 V
Mounting Type	Module
Communication Protocol	MODBUS
Number of Hardware Interfaces	Industrial Ethernet 0 Other 1 Parallel 0 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 0
Includes	Control unit PC connection
Analog Inputs	2
Analog Outputs	1
Number of Digital In/Outputs	4 / 2
Output Current, Normal	7.2 A
Use (I <sub>n</sub> )	

Output Current, Light-Overload Use ( $I_{LD}$ )	6.8 A
Output Current, Heavy-Duty Use ( $I_{HD}$ )	5.6 A
Output Power, Normal Use ( $P_n$ )	3 kW
Output Power, Light-Overload Use ( $P_{LD}$ )	3 kW
Output Power, Heavy-Duty Use ( $P_{HD}$ )	2.2 kW
Apparent Power Output	5 kV·A
Efficiency Level	IE2
Standby Loss	9 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	37 W	87.8 %	0.7 %
0/50 %	44 W	92.1 %	0.9 %
0/100 %	62 W	93.9 %	1.2 %
50/25 %	39 W	93.4 %	0.8 %
50/50 %	48 W	95.7 %	1.0 %
50/100 %	71 W	96.5 %	1.4 %
90/50 %	54 W	97.2 %	1.1 %
90/100 %	86 W	97.6 %	1.7 %

Temperature Rating Maximum 40 °C

## Technical UL

Output Current, Heavy-Duty Use (UL)	4.8 A
Output Current, Light-Overload Use (UL)	6.0 A
Output Power, Heavy-Duty Use (UL)	3 Hp
Output Power, Light-Overload Use (UL)	3 Hp

## Environmental

SCIP	5d07f008-496e-4abd-8f50-616cb485c791 Finland (FI)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Additional Information

Product Name	Frequency converter
--------------	---------------------

---

## Categories

---

Drives → Low Voltage AC Drives → Machinery Drives → ACS180 - Machinery Drive

