

Product datasheet

Specifications



LP1D400046SWS96 CONTACTOR

LP1D400046SWS96

⚠ Discontinued on: 6 July 2020

⚠ Discontinued

Main

Device short name LP1D

Complementary

Control circuit voltage limits 0.1...0.3 Uc (-40...70 °C):drop-out DC
0.75...1.2 Uc (-40...55 °C):operational DC
1...1.2 Uc (55...70 °C):operational DC

Environment

Permissible ambient air temperature around the device -40...60 °C
60...70 °C with derating

Operating altitude 0...3000 m

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 13.9 cm

Package 1 Width 17.5 cm

Package 1 Length 22.7 cm

Package 1 Weight 2.28 kg

Contractual warranty

Warranty (in months) 18

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins