

# Product datasheet

Specifications



## TeSys - LT3TK Thermal time delay protection relay 24 V

LT3TK024

⚠ Discontinued on: 31 Dec 2023

⚠ Discontinued

### Main

Range of the product	TeSys
Device short name	LT3TK
Product or component type	Relay
Device application	Protection
Relay application	Time delay relay

### Complementary

[Us] rated supply voltage	24 V AC/DC
Voltage range	0.85...1.1 Us
Contacts type and composition	2 C/O multi voltage
[I <sub>th</sub> ] conventional enclosed thermal current	5 A
Ambient air temperature for operation	-25...60 °C
Control type	Automatic reset Manual reset
Hold-in power consumption in W	29...40 W
Height	85 mm
Width	81 mm
Depth	80 mm

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.0 cm
Package 1 Width	13.5 cm
Package 1 Length	13.5 cm
Package 1 Weight	448.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	5
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm

---

Package 2 Weight	2.625 kg
------------------	----------

## Contractual warranty

---

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

EU RoHS Directive [Compliant](#)

### Use Longer



#### Lifetime extension

Repair **No**

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins