


Data sheet for dv/dt filter plus VPL

Article No. : 6SL3000-2DH33-3AA0



Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data	
------------	--

Output current	330 A
----------------	-------

General technical specifications		
----------------------------------	--	--

Power loss	dv/dt reactor	Voltage Peak Limiter (VPL)
at 690 V / 50 Hz	0.595 kW	0.042 kW
at 575 V / 60 Hz	0.620 kW	0.039 kW
at 690 V / 150 Hz	0.661 kW	0.036 kW

Connections	
-------------	--

Cable length	
--------------	--

for motor, max. (shielded)	300 m (984 ft)
for motor, max. (unshielded)	450 m (1,476 ft)

Design	dv/dt reactor	Voltage Peak Limiter (VPL)
Power cable	1 x hole for M10	-
Load	1 x hole for M10	-
PE conductor	M6 screw	35 mm2 terminals
dv/dt reactor	-	70 mm2 terminals
DC link	-	70 mm2 terminals

Mechanical data		
-----------------	--	--

Degree of protection	IP00	
----------------------	------	--

	dv/dt reactor	Voltage Peak Limiter (VPL)
Net weight	135 kg (298 lb)	16 kg (35 lb)

Dimensions		
------------	--	--

Width	460 mm (18.10 in)	392 mm (15.40 in)
Height	360 mm (14.20 in)	285 mm (11.20 in)
Depth	275 mm (10.80 in)	210 mm (8.27 in)

Standards	
-----------	--

Compliance with standards	CE, cURus
---------------------------	-----------