




UL 1077

T&B Catalog Number: S503-K15
 UPC Number: 66201936910
 Status: Active

Description:

3 pole, 10 - 15 amp rated at 600Y/277 VAC, UL 1077 series miniature circuit breaker with thermal-magnetic trip device, K trip curve, and 30kA interrupt current rating



Where To Buy

Enter Zip Code:

Enter Quantity:

Features

- High performance MCB provides compact supplementary, energy limiting, circuit protection
- Fast breaking time
- Bus connection system
- Finger safe terminals
- Suitable for reverse feed

Application

- For use as a supplemental protection device
- Designed for the higher inrush currents during system start of inductive loads: as in motor and transformer applications
- For use with inductive loads

General

Mounting Method	DIN Rail
Trip Type	Thermal-magnetic
Number of Poles	3
Series	S500-K
Terminal Type	Screw

Approvals

UL Class	UL 1077
----------	---------

Dimension Information

H x W x D (inches)	3.62 x 2.95 x 3.15
H x W x D (mm)	92 x 75 x 80

Specifications

Rated Current (Amps)	10 - 15
Rated Voltage AC	600Y/277
Interrupt Rating (kA)	30
Trip Curve	K

Packaging

Outer Package	1
Package Height	3.86
Package Length	5.91
Package Width	3.62
T&B Sold in UOM	Each
T&B Weight Per UOM	1.55 lbs. Each