

auxiliary switch, on the front, 2 NO + 2 NC, 53/54, 61/62, 71/72, 83/84, current path: 1 NO, 1 NC, 1 NC, 1 NO, spring-loaded terminal, for 3RT101...-K...-0LA0

product brand name	SIRIUS
product category	Auxiliary switch
product designation	auxiliary switch
design of the product	for snapping onto the front
product type designation	3RH19
suitability for use	Contactor relay and power contactor
General technical data	
size of contactor	S00
insulation voltage with degree of pollution 3 at AC rated value	690 V
surge voltage resistance rated value	6 kV
protection class IP on the front	IP20
mechanical service life (operating cycles) typical	10 000 000
electrical endurance (operating cycles) at AC-15 at 230 V typical	200 000
Net Weight	0.065 kg
number of NC contacts for auxiliary contacts	
• instantaneous contact	2
number of NO contacts for auxiliary contacts	
• instantaneous contact	2
number of CO contacts of auxiliary contacts instantaneous contact	0
operational current at AC-15 at 690 V rated value	1 A
operational current of auxiliary contacts at AC-12	
• at 24 V	10 A
• at 230 V	10 A
operational current of auxiliary contacts at AC-14	
• at 125 V	6 A
• at 250 V	6 A
operational current of auxiliary contacts at AC-12 maximum	10 A
operational current of auxiliary contacts at AC-15	
• at 24 V	6 A
• at 230 V	6 A
• at 400 V	3 A
operational current of auxiliary contacts at DC-12	
• at 24 V	10 A
• at 110 V	3 A
• at 220 V	1 A
operational current with 2 current paths in series at DC-12	
• at 24 V rated value	10 A
• at 60 V rated value	10 A
• at 110 V rated value	4 A
• at 220 V rated value	2 A
• at 440 V rated value	1.3 A
• at 600 V rated value	0.65 A
operational current with 3 current paths in series at DC-12	
• at 24 V rated value	10 A
• at 60 V rated value	10 A
• at 110 V rated value	10 A
• at 220 V rated value	3.6 A
• at 440 V rated value	2.5 A
• at 600 V rated value	1.8 A

operational current with 2 current paths in series at DC-13			
• at 24 V rated value	10 A		
• at 60 V rated value	3.5 A		
• at 110 V rated value	1.3 A		
• at 220 V rated value	0.9 A		
• at 440 V rated value	0.2 A		
• at 600 V rated value	0.1 A		
operational current with 3 current paths in series at DC-13			
• at 24 V rated value	10 A		
• at 60 V rated value	4.7 A		
• at 110 V rated value	3 A		
• at 220 V rated value	1.2 A		
• at 440 V rated value	0.5 A		
• at 600 V rated value	0.26 A		
operational current of auxiliary contacts at DC-13			
• at 24 V	6 A		
• at 48 V	2 A		
• at 60 V	2 A		
• at 110 V	1 A		
• at 125 V	0.9 A		
• at 220 V	0.3 A		
• at 250 V	0.3 A		
design of the miniature circuit breaker for short-circuit protection of the auxiliary circuit up to 230 V	C characteristic: 10 A; 0.4 kA		
contact reliability of auxiliary contacts	1 faulty switching per 100 million (17 V, 1 mA)		
Ambient conditions			
ambient temperature			
• during operation	-25 ... +60 °C		
• during storage	-55 ... +80 °C		
Safety related data			
product function			
• mirror contact according to IEC 60947-4-1	No		
• positively driven operation according to IEC 60947-5-1	No		
Short-circuit protection			
design of the miniature circuit breaker for short-circuit protection of the auxiliary circuit up to 230 V	C characteristic: 10 A; 0.4 kA		
design of the fuse link for short-circuit protection of the auxiliary switch required	gG: 10 A (500 V, 1 kA)		
Installation/ mounting/ dimensions			
fastening method	snap-on mounting		
height	37.5 mm		
width	36.5 mm		
depth	46 mm		
Connections/ Terminals			
type of electrical connection for auxiliary and control circuit	spring-loaded terminals		
connectable conductor cross-section for auxiliary contacts			
• solid or stranded	0.5 ... 2.5 mm²		
• finely stranded with core end processing	0.5 ... 2.5 mm²		
• finely stranded without core end processing	0.5 ... 2.5 mm²		
type of connectable conductor cross-sections			
• for auxiliary contacts			
— solid or stranded	2x (0.5 ... 2.5 mm²)		
— finely stranded with core end processing	2x (0.5 ... 1.5 mm²)		
— finely stranded without core end processing	2x (0.5 ... 2.5 mm²)		
• for AWG cables for auxiliary contacts	2x (20 ... 14)		
AWG number as coded connectable conductor cross section for auxiliary contacts	20 ... 14		
Approvals Certificates			
Environment	General Product Approval	Test Certificates	other



other

Railway



[Special Test Certific-
ate](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RH1911-2FA22-0MC0>

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RH1911-2FA22-0MC0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RH1911-2FA22-0MC0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RH1911-2FA22-0MC0&lang=en

last modified:

4/11/2025