

Product datasheet

Specifications



Switch disconnecter, MasterPact NW25HF, 2500A, 187kA/440VAC 50/60Hz (Icm), 4 poles, drawout

48311

Main

Range	MasterPacT
Product name	MasterPact NW
Product or component type	Switch disconnecter
Device short name	MasterPact NW25
Switch-disconnector name	MasterPact NW25HF
Device application	Protection
Poles description	4P
Network type	AC
Network frequency	50/60 Hz
[Ie] rated operational current	2500 A AC 50/60 Hz 690 V
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to IEC 60947-3
[Uimp] rated impulse withstand voltage	12 kV conforming to IEC 60947-3
[Icm] rated short-circuit making capacity	187 kA 220...690 V AC at 50/60 Hz
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-3
Breaking capacity code	HF
Suitability for isolation	Yes conforming to IEC 60947-3
Contact position indicator	Yes
Visible break	No
Pollution degree	4 conforming to IEC 60664-1

Complementary

Control type	Push-button
Mounting mode	Drawout
Mounting support	Chassis
Operating rate	10 cyc/h maximum
[Icw] rated short-time withstand current	85 kA during 1 s conforming to IEC 60947-3 75 kA during 3 s conforming to IEC 60947-3
Mechanical durability	10000 cycles without maintenance conforming to IEC 60947-3 20000 cycles with maintenance conforming to IEC 60947-3
Electrical durability	AC-3: 6000 cycles 440/690 V AC 50/60 Hz without maintenance conforming to IEC 60947-3 AC-23A: 2500 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-3 AC-23A: 5000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-3

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Connection pitch	115 mm
Height	352 mm
Width	537 mm
Depth	297 mm
Net weight	80 kg

Environment

Standards	IEC 60947-3
Product certifications	ASEFA ASTA
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-35...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.5 cm
Package 1 Width	29.5 cm
Package 1 Length	49.5 cm
Package 1 Weight	49.641 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	4 078 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint of the manufacturing phase [A1 to A3]	582 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	14 kg CO2 eq.
Carbon footprint of the installation phase [A5]	20 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	3 253 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	209 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards
SCIP Number	6a3c1e0b-44cb-4a11-80eb-a083722777c1
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes
Silicone-free	No

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	69
End of life manual availability	End of Life Information
Take-back	Yes
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins