


Product data sheet

Specifications



TeSys F - contactor coil - LX4FG - 48 V DC wide range

LX4FG040

⚠ Discontinued on: Jul 12, 2021

⚠ Discontinued

Main

Range	TeSys
Product or Component Type	Contactor coil
Device short name	LX4FG
Range compatibility	TeSys TeSys F LC1F contactor
Product Compatibility	LC1F185 LC1F225
Control circuit type	DC wide range
[Uc] control circuit voltage	48 V DC
Inductance of closed circuit	34.4 H
Average resistance	2 Ohm inrush 68 °F (20 °C) 359 Ohm holding 68 °F (20 °C)
Operating time	30...40 ms closing 30...50 ms opening
Mechanical durability	1 Mcycles
Maximum operating rate	60 cyc/h 158 °F (70 °C)

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Operational 0.7...1.25 Uc 158 °F (70 °C)) Drop-out 0.2...0.45 Uc 158 °F (70 °C))
Inrush power in W	800 W 68 °F (20 °C))
Hold-in power consumption in W	5 W 68 °F (20 °C)

Environment

Ambient Air Temperature for Operation	-67...158 °F (-55...70 °C)
Net Weight	1.21 lb(US) (0.55 kg)

Ordering and shipping details

Category	18401-WORLD SERVICE PARTS(CTR ACCESS)
Discount Schedule	CP10
GTIN	3389110247138
Returnability	No

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Nbr. of units in pkg.	1
-----------------------	---

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

[EU RoHS Directive](#)

Pro-active compliance (Product out of EU RoHS legal scope)

Use Longer



Lifetime extension

Repair

No