

Product data sheet

Specifications



ASCO 4500 Load Bank

ASCOLBLV4500

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Resistive load bank

Complementary

Voltage Rating	208 V AC 60 Hz, 3 phase 240/480 V AC 60 Hz, 3 phase 240 V AC 60 Hz, 3 phase 400 V AC 50 Hz, 3 phase 480 V AC 60 Hz, 3 phase 600 V AC 60 Hz, 3 phase
Capacity Rating	200 kW 225 kW 250 kW 300 kW 350 kW 400 kW 500 kW
Load Step Resolution	5 kW 50 kW
Cooling System Rating	5834899.02 Gal/hr(US) (22087.1 m3/h)
Provided Equipment	Switch 3 On-Off LED 2 on LED 1 alarm indication Cooling fans 1
Enclosure Material	Aluminium Steel
Surface Finish	Polyester powder
Color	Gray
Connection Terminals	Terminals inside)
Length	61.02 in (1550 mm)
Width	46.5 in (1181 mm)
Height	51.0 in (1295 mm)
Product Weight	1100.1 lb(US) (499 kg)

Environment

Ambient Air Temperature	-18...122 °F (-28...50 °C)
Standards	ISO 9001 NEMA UL 508 A

Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	61.02 in (155.0 cm)
Package 1 Width	46.5 in (118.1 cm)
Package 1 Length	51.0 in (129.5 cm)
Package weight(Lbs)	1100.1 lb(US) (499.0 kg)

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
--	-----

Packaging without single use plastic	No
--------------------------------------	----

Use Longer



Lifetime extension

Repair	No
--------	----