


Product datasheet

Specifications



auxiliary contact, Fupact ISFT100, 1 changeover contact NO/NC, 2A

49885

⚠ Discontinued on: 27 Aug 2020

⚠ End-of-service on: 30 Mar 2022

⚠ Discontinued

Main

Range	FuPact
Product or component type	Auxiliary contact
Device application	Remote indication
Range compatibility	FuPact ISFT100 fuse-switch disconnecter
Auxiliary contacts type	Standard
contact function	Changeover contact
Signal contacts composition	1 NO/NC
[Ith] conventional free air thermal current	2 A

Complementary

output contact breaking capacity	AC-12: 2 A at 24 V AC-12: 2 A at 48 V AC-12: 2 A at 110 V AC-12: 2 A at 220/240 V DC-12: 0.2 A at 24 V DC-12: 0.2 A at 48 V DC-12: 0.2 A at 110 V DC-12: 0.2 A at 220/240 V
Minimum load	100 mA at 24 V
[Ui] rated insulation voltage	250 V
Kit composition	Mounting accessory
Standards	IEC 60947-5-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.7 cm
Package 1 Width	10 cm
Package 1 Length	12 cm
Package 1 Weight	5 g

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins