

# Product data sheet

Specifications



## gearbox with straight teeth GBX- Ø 60 mm- reduction 4:1- < 16arcmin- 38 N.m

GBX0600040703F

⚠ Discontinued on: Aug 30, 2023

⚠ End-of-service on: Dec 31, 2023

⚠ Discontinued

## Main

Range compatibility	Lexium 32 Lexium 15
Product or component type	Planetary gearbox
Gear box type	Straight teeth
Device short name	GBX
Gearbox external diameter	2.4 in (60 mm)
Product compatibility	BSH0703...
Reduction ratio	4:1

## Complementary

Maximum torsional backlash	16 arc.min
Torsional rigidity	2.3 N.m/arcmin
Housing colour	Black
Housing material	Black anodized aluminium
Shaft material	C 45
Additional information	Lubricated for life
Service life in hours	30000 h 100 rpm 86 °F (30 °C)
Efficiency	96 %
Mounting position	Any position
Maximum radial force Fr	340 N 100 rpm, force applied at mid-distance from output shaft during 30000 hour at 30 °C 500 N 100 rpm, force applied at mid-distance from output shaft during 10000 hour at 30 °C
Maximum axial force Fa	450 N 100 rpm, during 30000 hour at 30 °C 600 N 100 rpm, during 10000 hour at 30 °C
moment of inertia	0.00003 lb.in <sup>2</sup> (0.093 g.cm <sup>2</sup> )
Continuous output torque	336.3 lbf.in (38 N.m) 100 rpm 86 °F (30 °C)
Maximum output torque	539.9 lbf.in (61 N.m) 100 rpm 86 °F (30 °C)
Net weight	2.0 lb(US) (0.9 kg)
Compatibility code	GBX

## Environment

Noise level	58 dB 1 m, no-load
-------------	--------------------

---

IP degree of protection	Shaft output IP54
-------------------------	-------------------

---

ambient temperature for operation	-13...194 °F (-25...90 °C)
-----------------------------------	----------------------------

---

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

## Contractual warranty

---

Warranty (in months)	18
----------------------	----

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No