


Product datasheet

Specifications



M2C programmable contacts, MasterPact MTZ1 drawout, 2 contacts, 3A/250VAC

LV847483

Main

Range	MasterPact
Device short name	M2c
Product or component type	Programmable contact
Device application	Safety logic controller
Range compatibility	MasterPact MTZ1 circuit-breaker
Number of contacts	2
Signal contacts composition	2 NO

Complementary

Circuit breaker mounting mode	Drawout
[Ie] rated operational current	3 A at 250 V AC 3 A at 30 V DC
Minimum load	10 mA at 5 V DC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	6.0 cm
Package 1 Length	8.2 cm
Package 1 Weight	69.0 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	7ad12b2f-38d8-4da7-8519-e4f93e0ce077
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer

Lifetime extension

Repair	No
--------	----

Use Again

Repack and remanufacture

Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins