



circuit breaker frame size S00 for motor protection, Class 10 thermal release  
0.14...0.2 A short-circuit release 2.6 A screw terminal standard switching capacity  
with transverse auxiliary switch 1 NO+1 NC

|                                                                                                |                        |
|------------------------------------------------------------------------------------------------|------------------------|
| product brand name                                                                             | SIRIUS                 |
| product designation                                                                            | Circuit breaker        |
| design of the product                                                                          | For motor protection   |
| product type designation                                                                       | 3RV2                   |
| <b>General technical data</b>                                                                  |                        |
| Product equipment of circuit breaker for motor protection complete unit with protection device | Yes                    |
| size of the circuit-breaker                                                                    | S00                    |
| size of contactor can be combined company-specific                                             | S00, S0                |
| product function disconnecter functionality                                                    | Yes                    |
| product extension auxiliary switch                                                             | Yes                    |
| power loss [W] for rated value of the current                                                  |                        |
| • at AC in hot operating state                                                                 | 5.5 W                  |
| • at AC in hot operating state per pole                                                        | 1.8 W                  |
| type of calculation of power loss current-dependent                                            | quadratic              |
| insulation voltage with degree of pollution 3 at AC rated value                                | 690 V                  |
| surge voltage resistance rated value                                                           | 6 kV                   |
| maximum permissible voltage for protective separation                                          |                        |
| • in networks with ungrounded star point between main and auxiliary circuit                    | 400 V                  |
| • in networks with grounded star point between main and auxiliary circuit                      | 400 V                  |
| protection class IP                                                                            |                        |
| • on the front according to IEC 60529                                                          | IP20                   |
| • on the front                                                                                 | IP20                   |
| • of the terminal                                                                              | IP20                   |
| shock resistance according to IEC 60068-2-27                                                   | 25g / 11 ms            |
| mechanical service life (operating cycles)                                                     |                        |
| • of the main contacts typical                                                                 | 100 000                |
| • of auxiliary contacts typical                                                                | 100 000                |
| electrical endurance (operating cycles) typical                                                | 100 000                |
| reference code according to IEC 81346-2                                                        | Q                      |
| continuous current rated value                                                                 | 0.2 A                  |
| Substance Prohibitance (day/month/year)                                                        | 10/01/2009             |
| SVHC substance name                                                                            | Lead CAS-No. 7439-92-1 |
| Net Weight                                                                                     | 294 g                  |
| <b>Ambient conditions</b>                                                                      |                        |

|                                                                                            |                |
|--------------------------------------------------------------------------------------------|----------------|
| installation altitude at height above sea level maximum                                    | 2 000 m        |
| <b>ambient temperature</b>                                                                 |                |
| • during operation                                                                         | -20 ... +60 °C |
| • during storage                                                                           | -50 ... +80 °C |
| • during transport                                                                         | -50 ... +80 °C |
| <b>temperature compensation</b>                                                            | -20 ... +60 °C |
| relative humidity during operation                                                         | 10 ... 95 %    |
| <b>Main circuit</b>                                                                        |                |
| <b>number of poles for main current circuit</b>                                            | 3              |
| <b>adjustable current response value current of the current-dependent overload release</b> | 0.14 ... 0.2 A |
| <b>type of voltage for main current circuit</b>                                            | AC             |
| <b>operating voltage</b>                                                                   |                |
| • rated value                                                                              | 690 V          |
| • rated value                                                                              | 20 ... 690 V   |
| • at AC-3 rated value maximum                                                              | 690 V          |
| • at AC-3e rated value maximum                                                             | 690 V          |
| <b>operating frequency rated value</b>                                                     | 50 ... 60 Hz   |
| <b>operational current rated value</b>                                                     | 0.2 A          |
| <b>operational current</b>                                                                 |                |
| • at AC-3 at 400 V rated value                                                             | 0.2 A          |
| • at AC-3e at 400 V rated value                                                            | 0.2 A          |
| <b>operating power</b>                                                                     |                |
| • at AC-3                                                                                  |                |
| — at 230 V rated value                                                                     | 0 kW           |
| — at 400 V rated value                                                                     | 0.06 kW        |
| — at 500 V rated value                                                                     | 0.1 kW         |
| — at 690 V rated value                                                                     | 0.1 kW         |
| • at AC-3e                                                                                 |                |
| — at 230 V rated value                                                                     | 0 kW           |
| — at 400 V rated value                                                                     | 0.06 kW        |
| — at 500 V rated value                                                                     | 0.1 kW         |
| — at 690 V rated value                                                                     | 0.1 kW         |
| <b>operating frequency</b>                                                                 |                |
| • at AC-3 maximum                                                                          | 15 1/h         |
| • at AC-3e maximum                                                                         | 15 1/h         |
| <b>Auxiliary circuit</b>                                                                   |                |
| <b>design of the auxiliary switch</b>                                                      | transverse     |
| <b>type of voltage for auxiliary and control circuit</b>                                   | AC/DC          |
| <b>number of NC contacts for auxiliary contacts</b>                                        | 1              |
| <b>number of NO contacts for auxiliary contacts</b>                                        | 1              |
| number of CO contacts for auxiliary contacts                                               | 0              |
| <b>operational current of auxiliary contacts at AC-15</b>                                  |                |
| • at 24 V                                                                                  | 2 A            |
| • at 120 V                                                                                 | 0.5 A          |
| • at 125 V                                                                                 | 0.5 A          |
| • at 230 V                                                                                 | 0.5 A          |
| <b>operational current of auxiliary contacts at DC-13</b>                                  |                |
| • at 24 V                                                                                  | 1 A            |
| • at 60 V                                                                                  | 0.15 A         |
| <b>Protective and monitoring functions</b>                                                 |                |
| <b>product function</b>                                                                    |                |
| • ground fault detection                                                                   | No             |
| • phase failure detection                                                                  | Yes            |
| <b>trip class</b>                                                                          | CLASS 10       |
| <b>design of the overload release</b>                                                      | thermal        |
| <b>protection function thermal overload protection (ANSI 49)</b>                           | Yes            |
| <b>maximum short-circuit current breaking capacity (Icu)</b>                               |                |
| • at AC at 240 V rated value                                                               | 100 kA         |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at AC at 400 V rated value</li> <li>• at AC at 500 V rated value</li> <li>• at AC at 690 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 100 kA                                                                                                                                                                                           |
| operating short-circuit current breaking capacity (Ics) at AC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at 240 V rated value</li> <li>• at 400 V rated value</li> <li>• at 500 V rated value</li> <li>• at 690 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 100 kA                                                                                                                                                                                           |
| response value current of instantaneous short-circuit trip unit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 2.6 A                                                                                                                                                                                            |
| <b>UL/CSA ratings</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                                                                                                                  |
| full-load current (FLA) for 3-phase AC motor                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• at 480 V rated value</li> <li>• at 600 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 0.2 A                                                                                                                                                                                            |
| contact rating of auxiliary contacts according to UL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | C300 / R300                                                                                                                                                                                      |
| UL File Number (CCN)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | E47705 (NLRV, NLRV7), E156943 (NKJH, NKJH7)                                                                                                                                                      |
| <b>Short-circuit protection</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                  |
| product function short circuit protection                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Yes                                                                                                                                                                                              |
| design of the short-circuit trip                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | magnetic                                                                                                                                                                                         |
| design of the fuse link                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• for short-circuit protection of the auxiliary switch required</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Fuse gL/gG: 10 A, miniature circuit breaker C 6 A (short-circuit current I <sub>k</sub> < 400 A)                                                                                                 |
| certificate of suitability according to ATEX directive 2014/34/EU                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | DMT 02 ATEX F 001                                                                                                                                                                                |
| type of protection according to ATEX directive 2014/34/EU                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Ex II (2) GD                                                                                                                                                                                     |
| <b>Installation/ mounting/ dimensions</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                                  |
| mounting position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | any                                                                                                                                                                                              |
| fastening method                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 60715                                                                                                                         |
| Mounting method of circuit breaker for Transformer protection, Generator protection and system protection optional standard bar mounting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Yes                                                                                                                                                                                              |
| height                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 97 mm                                                                                                                                                                                            |
| width                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 45 mm                                                                                                                                                                                            |
| depth                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 97 mm                                                                                                                                                                                            |
| required spacing                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                  |
| <ul style="list-style-type: none"> <li>• with side-by-side mounting <ul style="list-style-type: none"> <li>— forwards</li> <li>— backwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> <li>• for grounded parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— backwards</li> <li>— upwards</li> <li>— at the side</li> <li>— downwards</li> </ul> </li> <li>• for live parts <ul style="list-style-type: none"> <li>— forwards</li> <li>— backwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> <li>• for grounded parts at 400 V <ul style="list-style-type: none"> <li>— downwards</li> <li>— upwards</li> <li>— at the side</li> </ul> </li> <li>• for live parts at 400 V <ul style="list-style-type: none"> <li>— downwards</li> <li>— upwards</li> <li>— at the side</li> </ul> </li> <li>• for grounded parts at 500 V</li> </ul> | 0 mm<br>0 mm<br>50 mm<br>50 mm<br>0 mm<br><br>0 mm<br>0 mm<br>50 mm<br>30 mm<br>50 mm<br><br>0 mm<br>0 mm<br>50 mm<br>50 mm<br>30 mm<br><br>30 mm<br>30 mm<br>9 mm<br><br>30 mm<br>30 mm<br>9 mm |

|                                                                                       |                                                                       |
|---------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
| — downwards                                                                           | 30 mm                                                                 |
| — upwards                                                                             | 30 mm                                                                 |
| — at the side                                                                         | 9 mm                                                                  |
| • for live parts at 500 V                                                             |                                                                       |
| — downwards                                                                           | 30 mm                                                                 |
| — upwards                                                                             | 30 mm                                                                 |
| — at the side                                                                         | 9 mm                                                                  |
| • for grounded parts at 690 V                                                         |                                                                       |
| — downwards                                                                           | 50 mm                                                                 |
| — upwards                                                                             | 50 mm                                                                 |
| — backwards                                                                           | 0 mm                                                                  |
| — at the side                                                                         | 30 mm                                                                 |
| — forwards                                                                            | 0 mm                                                                  |
| • for live parts at 690 V                                                             |                                                                       |
| — downwards                                                                           | 50 mm                                                                 |
| — upwards                                                                             | 50 mm                                                                 |
| — backwards                                                                           | 0 mm                                                                  |
| — at the side                                                                         | 30 mm                                                                 |
| — forwards                                                                            | 0 mm                                                                  |
| <b>Connections/ Terminals</b>                                                         |                                                                       |
| <b>product component removable terminal for auxiliary and control circuit</b>         | No                                                                    |
| <b>type of electrical connection</b>                                                  |                                                                       |
| • for main current circuit                                                            | screw-type terminals                                                  |
| • for auxiliary and control circuit                                                   | screw-type terminals                                                  |
| <b>arrangement of electrical connectors for main current circuit</b>                  | Top and bottom                                                        |
| <b>type of connectable conductor cross-sections</b>                                   |                                                                       |
| • for main contacts                                                                   |                                                                       |
| — solid or stranded                                                                   | 2x (0,75 ... 2,5 mm <sup>2</sup> ), 2x 4 mm <sup>2</sup>              |
| — finely stranded with core end processing                                            | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> ) |
| • for AWG cables for main contacts                                                    | 2x (18 ... 14), 2x 12                                                 |
| <b>connectable conductor cross-section for main contacts</b>                          |                                                                       |
| • solid or stranded                                                                   | 0.75 ... 4 mm <sup>2</sup>                                            |
| • finely stranded with core end processing                                            | 0.5 ... 2.5 mm <sup>2</sup>                                           |
| <b>connectable conductor cross-section for auxiliary contacts</b>                     |                                                                       |
| • solid or stranded                                                                   | 0.5 ... 2.5 mm <sup>2</sup>                                           |
| • finely stranded with core end processing                                            | 0.5 ... 2.5 mm <sup>2</sup>                                           |
| <b>type of connectable conductor cross-sections</b>                                   |                                                                       |
| • for auxiliary contacts                                                              |                                                                       |
| — solid or stranded                                                                   | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> ) |
| — finely stranded with core end processing                                            | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> ) |
| • for AWG cables for auxiliary contacts                                               | 2x (20 ... 16), 2x (18 ... 14)                                        |
| <b>AWG number as coded connectable conductor cross section for main contacts</b>      | 18 ... 12                                                             |
| <b>AWG number as coded connectable conductor cross section for auxiliary contacts</b> | 20 ... 14                                                             |
| <b>tightening torque</b>                                                              |                                                                       |
| • for main contacts with screw-type terminals                                         | 0.8 ... 1.2 N·m                                                       |
| • for auxiliary contacts with screw-type terminals                                    | 0.8 ... 1.2 N·m                                                       |
| <b>design of screwdriver shaft</b>                                                    | Diameter 5 to 6 mm                                                    |
| <b>size of the screwdriver tip</b>                                                    | Pozidriv size 2                                                       |
| <b>design of the thread of the connection screw</b>                                   |                                                                       |
| • for main contacts                                                                   | M3                                                                    |
| • of the auxiliary and control contacts                                               | M3                                                                    |
| <b>Safety related data</b>                                                            |                                                                       |
| <b>product function suitable for safety function</b>                                  | Yes                                                                   |
| <b>suitability for use</b>                                                            |                                                                       |
| • safety-related switching on                                                         | No                                                                    |
| • safety-related switching OFF                                                        | Yes                                                                   |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                                                             |                                                                                                                                                                                                             |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| service life maximum                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 10 a                                                                                                                        |                                                                                                                                                                                                             |
| test wear-related service life necessary                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Yes                                                                                                                         |                                                                                                                                                                                                             |
| proportion of dangerous failures <ul style="list-style-type: none"><li>• with low demand rate according to SN 31920</li><li>• with high demand rate according to SN 31920</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 40 %<br>50 %                                                                                                                |                                                                                                                                                                                                             |
| B10 value with high demand rate according to SN 31920                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 5 000                                                                                                                       |                                                                                                                                                                                                             |
| failure rate [FIT] with low demand rate according to SN 31920                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 50 FIT                                                                                                                      |                                                                                                                                                                                                             |
| ISO 13849                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                             |                                                                                                                                                                                                             |
| device type according to ISO 13849-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 3                                                                                                                           |                                                                                                                                                                                                             |
| overdimensioning according to ISO 13849-2 necessary                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Yes                                                                                                                         |                                                                                                                                                                                                             |
| IEC 61508                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                             |                                                                                                                                                                                                             |
| safety device type according to IEC 61508-2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Type A                                                                                                                      |                                                                                                                                                                                                             |
| T1 value <ul style="list-style-type: none"><li>• for proof test interval or service life according to IEC 61508</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 10 a                                                                                                                        |                                                                                                                                                                                                             |
| Electrical Safety                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                             |                                                                                                                                                                                                             |
| protection class IP on the front according to IEC 60529                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | IP20                                                                                                                        |                                                                                                                                                                                                             |
| touch protection on the front according to IEC 60529                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | finger-safe, for vertical contact from the front                                                                            |                                                                                                                                                                                                             |
| Display                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                             |                                                                                                                                                                                                             |
| display version for switching status                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Handle                                                                                                                      |                                                                                                                                                                                                             |
| Approvals Certificates                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                             |                                                                                                                                                                                                             |
| Environmental Product Declaration                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                             |                                                                                                                                                                                                             |
| <ul style="list-style-type: none"><li>• global warming potential [CO2 eq] / during manufacturing</li><li>• global warming potential [CO2 eq] / during sales</li><li>• global warming potential [CO2 eq] / during operation</li><li>• global warming potential [CO2 eq] / after end of life</li><li>• global warming potential [CO2 eq] / total</li></ul>                                                                                                                                                                                                                                                                                                  | 1.98 kg<br>0.134 kg<br>72.7 kg<br>-0.116 kg<br>74.698 kg                                                                    |                                                                                                                                                                                                             |
| Environment                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | General Product Approval                                                                                                    |                                                                                                                                                                                                             |
| <div><div><a href="#">Environmental Confirmations</a></div><div></div><div></div><div></div><div></div><div></div><div></div></div> |                                                                                                                             |                                                                                                                                                                                                             |
| General Product Approval                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                             |                                                                                                                                                                                                             |
| <div><div></div><div></div><div></div><div></div><div></div><div></div></div>                                                       |                                                                                                                             |                                                                                                                                                                                                             |
| For use in hazardous locations                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Test Certificates                                                                                                           | Maritime application                                                                                                                                                                                        |
| <div><div></div><div></div></div>                                                                                                                                                                                                                                                                                                                                                                                                                                                   | <div><div><a href="#">Special Test Certificate</a></div><div><a href="#">Type Test Certificates/Test Report</a></div></div> | <div><div></div><div></div></div> |
| Maritime application                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | other                                                                                                                       |                                                                                                                                                                                                             |
| <div><div></div><div></div><div></div><div></div></div>                                                                                                                                                                                                                                                       | <div><div><a href="#">Miscellaneous</a></div><div><a href="#">Confirmation</a></div></div>                                  |                                                                                                                                                                                                             |
| other                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Railway                                                                                                                     |                                                                                                                                                                                                             |



## Further information

## Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

## Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

## Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

## Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RV2011-0BA15>

## Service&amp;Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RV2011-0BA15>

## Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RV2011-0BA15&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RV2011-0BA15&lang=en)

## Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RV2011-0BA15>

## Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP='HAUPT'></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP='HAUPT'></mmp_prod_no>)



