

Cable D-Sub/end sleeve shie. 32x0.34 1m

connection cable shielded f. SIMATIC ET200 SP HA from 37-pole D-sub to bare ends with wire end sleeve labeled 32 channels L = 1 m, 0.34 mm²



| | |
|---|---|
| Technical Product Detail Page | https://i.siemens.com/1P6ES7923-3BB00-0HC0 |
| target system | SIMATIC ET 200SP HA |
| suitability for use | I/O modules |
| product type designation | Modular connection |
| product designation | Pre-assembled round cable |
| Operating data / header | |
| operating voltage / at DC | |
| • rated value | 24 V |
| • maximum | 60 V |
| ambient temperature | |
| • during operation | -30 ... +70 °C |
| • during storage | -30 ... +70 °C |
| General data / header | |
| suitability for interaction | |
| • input card PLC | Yes |
| • PLC output card | Yes |
| suitability for use | |
| • digital signal transmission | Yes |
| • analog signal transmission | Yes |
| Product properties, functions, components / general / header | |
| number of channels | 32 |
| design of cable | Round cable |
| wire length | 1 m |
| number of poles | 32 |
| number of conductors / of connection cable | 32 |
| conductor cross section / rated value | 0.34 mm ² |
| color / of cable sheath | Black |
| outer diameter / of cable sheath | 11 mm |
| material / of the connection cable sheath | PVC |
| marking / of cores | label clip |
| design of the shield | braided shield |
| connector type | D-Sub connector |
| type of electrical connection / on enclosure | Female header |
| number of poles / at the 1st interface | 37; control page |
| type of electrical connection / in the field | End sleeve |
| number of poles / at the 2nd interface | 32; numbered |
| certificate of suitability | |
| • cULus approval | No |
| net weight | 0.4 kg |

last modified:

11/14/2025 