

Product datasheet

Specifications



AC servo motor BDH - 1.2 N.m - 8000 rpm - key shaft - without brake - IP67

BDH0701E35A2A

⚠ Discontinued on: 8 Jul 2022

⚠ Discontinued

EAN Code: 3389118172050

Main

Product or component type	AC servo motors
Component name	BDH
Continuous stall torque	1.2 N.m for LXM15LD13M3 3 phases 1.2 N.m for LXM15LD13M3 single phase
Peak stall torque	3.24 N.m for LXM15LD13M3 at 230 V 3 phases 3.24 N.m for LXM15LD13M3 at 230 V single phase
Nominal output power	650 W for LXM15LD13M3 at 230 V 3 phases 650 W for LXM15LD13M3 at 230 V single phase
Nominal torque	1.2 N.m for LXM15LD13M3 at 230 V 3 phases 1.2 N.m for LXM15LD13M3 at 230 V single phase
Nominal speed	5000 rpm for LXM15LD13M3 at 230 V 3 phases 5000 rpm for LXM15LD13M3 at 230 V single phase
Maximum mechanical speed	8000 rpm
Product compatibility	LXM15LD13M3 at 230 V 3 phases LXM15LD13M3 at 230 V single phase
Shaft end	Keyed
IP degree of protection	IP67
Encoder type	2-pole resolver
Speed feedback resolution	65536 points/turn
Holding brake	Without
Mounting support	International IEC standard flange
Electrical connection	Rotatable right-angled connectors
Number of poles	8

Complementary

Range compatibility	Lexium 15
Maximum current Irms	8.48 A
Torque constant	0.41 N.m/A at 120 °C
Back emf constant	26.1 V/krpm at 120 °C
Stator resistance	4.58 Ohm at 20 °C
Stator inductance	8.6 mH at 20 °C
Stator electrical time constant	1.88 ms at 20 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Maximum radial force Fr	150 N at 6000 rpm
	165 N at 5000 rpm
	180 N at 4000 rpm
	200 N at 3000 rpm
	240 N at 2000 rpm
	300 N at 1000 rpm
Maximum axial force Fa	0.3 x Fr
Net weight	1.55 kg



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No