

Product datasheet

Specifications

contactor coil - FK - 300 V DC



LX4FL300

⚠ Discontinued on: Jun 30, 2020 AD

⚠ Discontinued

Main

Range	TeSys
Product or component type	Contactor coil
Device short name	LX4FL
Range compatibility	TeSys TeSys F LC1F contactor
Product compatibility	LC1F1250 LC1F630
Control circuit type	DC low consumption
[Uc] control circuit voltage	300 V DC
Operating time	40...50 ms opening 60...70 ms closing

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out: 0.2...0.35 Uc (at 55 °C) Operational: 0.85...1.1 Uc (at 55 °C)

Environment

Ambient air temperature for operation	-5...55 °C
---------------------------------------	------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.8 cm
Package 1 Width	11.4 cm
Package 1 Length	22.5 cm
Package 1 Weight	1.45 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained](#) >

[How we assess product sustainability](#) >



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Longer



Lifetime extension

Repair

No