

# Product data sheet

Specifications



## MX opening voltage release - 24 V AC - 24/30 V DC - for MTZ drawout

LV839233

⚠ Discontinued on: Sep 15, 2025

⚠ To be discontinued

### Main

|                           |                                                                                                                                        |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Device short name         | MX                                                                                                                                     |
| Product or Component Type | Voltage release                                                                                                                        |
| Device Application        | Control                                                                                                                                |
| Range compatibility       | Masterpact MasterPact MTZ2 circuit-breaker<br>Masterpact MasterPact MTZ3 circuit-breaker<br>Masterpact MasterPact MTZ1 circuit-breaker |
| Voltage release type      | Opening coil                                                                                                                           |

### Complementary

|                              |                                                                                                    |
|------------------------------|----------------------------------------------------------------------------------------------------|
| [Uc] control circuit voltage | 24 V AC 50/60 Hz<br>24...30 V DC                                                                   |
| Threshold tripping voltage   | 0.7...1.1 Un                                                                                       |
| Supply holding power         | 4.5 VA<br>4.5 W                                                                                    |
| Mounting Mode                | Drawout                                                                                            |
| Response time                | 50 ms +/- 10 % MasterPact MTZ1<br>50 ms +/- 10 % MasterPact MTZ2<br>50 ms +/- 10 % MasterPact MTZ3 |

### Ordering and shipping details

|      |               |
|------|---------------|
| GTIN | 3606489475369 |
|------|---------------|

### Packing Units

|                        |     |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
| Nbr. of units in pkg.  | 1   |

### Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

| Materials and Substances               |     |
|----------------------------------------|-----|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic   | No  |

### Use Longer

| Lifetime extension |    |
|--------------------|----|
| Repair             | No |

### Use Again

| Repack and remanufacture |    |
|--------------------------|----|
| Take-back                | No |