

Product data sheet

Specifications



RS422 converter for adapting 24 V control signals to RS422 standard

VW3M3102

⚠ Discontinued on: 13 Sept 2023

⚠ Discontinued

Main

Accessory / separate part type	Converter
Accessory / separate part category	Connection accessory
Accessory / separate part destination	RS422 interface
Product specific application	For adapting 24 V control signals to RS422 standard

Complementary

Range compatibility	Lexium 05
---------------------	-----------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.5 cm
Package 1 Width	17.0 cm
Package 1 Length	24.0 cm
Package 1 Weight	256.0 g
Unit Type of Package 2	S04
Number of Units in Package 2	12
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	4.324 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
PVC free	Yes

Use Longer

Lifetime extension	
Repair	No