

Product datasheet

Specifications



universal protection relay,
PowerLogic P3U 3CT CSH 1VT 8DI
8DO 48-230V DI220V 2RJ45 RL

REL53157

Main

Range of product	PowerLogic P3
Product or component type	Protection relay
Relay application	Universal
product reference	P3U20-6CAA3AHAA
Mounting case size	30TE
Device mounting	Flush
Mounting mode	Flush mounting
power supply	48...230 V AC/DC
measuring inputs	: 1/5 A CT phase current 3 : CSH residual current 1 : 100 V/110 V VT voltage 1
Number of sensors	0 temperature sensor(s)
number of Digital Inputs (DI)	8
number of analogue inputs	0
number of Digital Outputs (DO)	8 DO 1 watchdog
number of analogue outputs	0
communication ports	USB port 1 front RJ45 2 rear
communication protocols	IEC 61850 ed. 1 IEC 61850 ed. 2 IEC 60870-5-101 DNP3 TCP Modbus TCP EtherNet/IP
Redundancy communication port protocol	RSTP PRP
Cybersecurity	Password protection Port hardening

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

protection functions	Phase overcurrent 50/51 Earth fault overcurrent 50N/51N Directional earth fault 67N Transient earth fault 67NI Capacitor bank unbalance 51C Broken conductor 46 I2/I1 Cold load pick-up H2 detection 68H2 H5 detection 68H5 Breaker failure 50BF Switch ON to fault (SOTF) Recloser 79 Phase undercurrent 37 Excessive starting time, locked rotor 48/51LR Motor restart inhibition 66 Capacitor overvoltage 59C Negative sequence overcurrent 46 Earth fault overvoltage 59N Rate of change of frequency 81R Lockout relay 86 CT supervision 60 VT supervision 60 Programmable stages 99 8 Programmable curve Programmable logic
Arc flash protection	No
measurement functions	Current 3-phase Current zero sequence Current positive sequence Current negative sequence Current ratio of negative and positive Voltage zero sequence Earth fault reactance Frequency Current phasor diagram view Frequency 3-phase Current 2nd, 15th harmonics with THD Condition monitoring CB wear
control functions	Switchgear control and monitoring Programmable switchgear interlocking Local control on single-line diagram Local control with I/O keys Local/remote control 2 function keys Mobile application with Easergy SmartApp Web-server Programmable logic
controllable switchgear devices	4 controlled + 4 displayed
number of setting groups	4
monitoring functions	Trip circuit supervision 74 Circuit breaker monitoring Relay self-monitoring
logs and records	Event recording Disturbance recording Tripping context
Switchgear diagnosis type	CT supervision Trip circuit supervision ANSI code: TCS
Connections - terminals	Screw removable (digital input/output) Ring lugs removable (current transformer)

Complementary

Operating threshold	220 V AC/DC
Time synchronisation protocol	SNTP
Software name	ESetup Easergy Pro: virtual simulation test Easergy SmartApp

Web server	Embedded HTTP server
Display type	LCD 128 x 64 pixels with single line diagram
Number of key	2 customizable
Local signalling	4 LEDs 8 LEDs programmable
Height	169.5 mm
Width	170 mm
Depth	205 mm
Net weight	2.5 kg maximum

Environment

climatic withstand	Exposure to dry heat Bd tests conforming to EN/IEC 60068-2-2 Exposure to cold Ad tests conforming to EN/IEC 60068-2-1 Exposure to damp heat in service Db tests conforming to EN/IEC 60068-2-30 Exposure to damp heat in service Cab tests conforming to EN/IEC 60068-2-78
Mechanical robustness	Vibrations (level: class II) conforming to IEC 60255-21-1 Vibrations: Fc conforming to IEC 60068-2-6 Shocks (level: class II) conforming to IEC 60255-21-2 Shocks: Ea conforming to IEC 60068-2-27 Seismic tests method A (level: class II) conforming to IEC 60255-21-3
Electromagnetic compatibility	Emission tests conforming to IEC/EN 60255-26 ed. 3 Emission tests conforming to CISPR 11 Emission tests conforming to CISPR 22 Emission tests class A conforming to EN 55022 Emission tests class A conforming to EN 55011 Emission tests conforming to IEC 60255-25 EMC immunity conforming to IEC/EN 60255-26 ed. 3 EMC immunity conforming to EN/IEC 61000-4-18 EMC immunity conforming to IEC 60255-22-1 EMC immunity level 4 conforming to EN/IEC 61000-4-2 EMC immunity conforming to IEC 60255-22-2 EMC immunity level 3 conforming to EN/IEC 61000-4-3 EMC immunity conforming to IEC 60255-22-3 EMC immunity level 4 conforming to EN/IEC 61000-4-4 EMC immunity conforming to IEC 60255-22-4 EMC immunity level 3 conforming to EN/IEC 61000-4-5 EMC immunity conforming to IEC 60255-22-5 EMC immunity level 3 conforming to EN/IEC 61000-4-6 EMC immunity conforming to IEC 60255-22-6 EMC immunity conforming to EN/IEC 61000-4-8 EMC immunity level 5 conforming to EN/IEC 61000-4-9 EMC immunity conforming to EN/IEC 61000-4-29 EMC immunity conforming to EN/IEC 61000-4-11 EMC immunity conforming to EN/IEC 61000-4-17 EMC immunity conforming to IEC 60255-27 EMC immunity conforming to EN 60255-27 EMC immunity class III conforming to IEC 60255-5 EMC immunity conforming to EN/IEC 60255-1
Ambient air temperature for operation	-40...65 °C
IP degree of protection	IP54 front
maximum operating altitude	2000 m
Protective treatment	Conformal coating
Relative humidity	0...95 %, without condensation

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	40 cm

Package 1 Width	30 cm
Package 1 Length	30 cm
Package 1 Weight	3.8 kg

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	731 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	95 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	624 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	8 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	7fd15df9-a702-4a28-ad01-afb36a7b785f
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	32
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins