

\*\*\*\*\* spare part \*\*\*\*\* SIMATIC S7-400, fan subassembly for rack with 18 slots, 120/230 V AC



Figure similar

Supply voltage	
Rated value (AC)	
• 120 V AC	Yes
• 230 V AC	Yes
Line frequency	
• permissible range, lower limit	47 Hz
• permissible range, upper limit	63 Hz
Input current	
Inrush current, typ.	0.6 A at rated voltage 230 V AC; 1.15 A: at rated voltage 120 V AC
Power loss	
Power loss, max.	20 W
Digital outputs	
Relay outputs	
• Rated supply voltage of relay coil L+ (DC)	24 V
Switching capacity of contacts	
— with resistive load, max.	200 mA
Dimensions	
Width	482.5 mm
Height	109.5 mm
Depth	235 mm
Weights	
Weight, approx.	2 000 g
Classifications	

	Version	Classification
eClass	14	27-24-22-92
eClass	12	27-24-22-92
eClass	9.1	27-24-22-92
eClass	9	27-24-22-92
eClass	8	27-24-92-90
eClass	7.1	27-24-92-90
eClass	6	27-24-92-90
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552

## Approvals / Certificates

## General Product Approval

[Miscellaneous](#)

## General Product Approval

## EMV

## Maritime application

[China RoHS](#)[Miscellaneous](#)

## Maritime application

[CCS \(China Classification Society\)](#)

last modified:

7/21/2025