

# LADR26

Time delay auxiliary contact block, TeSys  
Deca, 1NO + 1NC, off delay 1-30s, front, lugs-  
ring terminals



## Main

|                                             |                                                                                                  |
|---------------------------------------------|--------------------------------------------------------------------------------------------------|
| Range                                       | TeSys<br>TeSys Deca                                                                              |
| Product name                                | TeSys D<br>TeSys Deca                                                                            |
| Product or Component Type                   | Time delay auxiliary contact block                                                               |
| Range compatibility                         | TeSys D CAD<br>TeSys D LC1D<br>TeSys F LC1F<br>TeSys F CR1F<br>TeSys Deca CAD<br>TeSys Deca LC1D |
| Mounting Location                           | Front                                                                                            |
| Pole contact composition                    | 1 NO + 1 NC                                                                                      |
| Contacts operation                          | Time delay                                                                                       |
| Timer type                                  | Off delay                                                                                        |
| Time delay range                            | 1...30 s                                                                                         |
| [Ue] rated operational voltage              | 690 V AC 25...400 Hz                                                                             |
| [Ie] rated operational current              | 120 V AC-15                                                                                      |
| [Ui] rated insulation voltage               | 690 V IEC 60947-5-1<br>600 V UL<br>600 V CSA                                                     |
| [Ith] conventional free air thermal current | 10 A 140 °F (60 °C)                                                                              |
| Standards                                   | UL 60947-5-1<br>CSA C22.2 No 60947-5-1<br>GB/T 14048.5<br>EN/IEC 60947-5-1<br>UL 60947-5-1       |
| Product certifications                      | CB<br>UL<br>CSA<br>CCC<br>EAC<br>UKCA                                                            |

## Complementary

|                               |                                                                                                                               |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Irms rated making capacity    | 140 A AC<br>250 A DC                                                                                                          |
| Permissible short-time rating | 100 A 140 °F (60 °C) 1 s<br>120 A 140 °F (60 °C) 500 ms<br>140 A 140 °F (60 °C) 100 ms                                        |
| Protection type               | GG fuse 10 A                                                                                                                  |
| Mechanical durability         | 5 Mcycles                                                                                                                     |
| Minimum switching current     | 5 mA                                                                                                                          |
| Minimum switching voltage     | 17 V                                                                                                                          |
| Non-overlap time              | 1.5 Ms on de-energisation no overlap between NC and NO contact<br>1.5 ms on energisation no overlap between NC and NO contact |
| Insulation resistance         | > 10 MOhm                                                                                                                     |
| Connections - terminals       | Lugs-ring terminals 0.31 in (8 mm))                                                                                           |

|                   |                                                                                                                   |
|-------------------|-------------------------------------------------------------------------------------------------------------------|
| Tightening torque | 15.05 Lbf.In (1.7 N.m) flat Ø 6 mm<br>15.05 Lbf.In (1.7 N.m) Philips No 2<br>15.05 lbf.in (1.7 N.m) pozidriv No 2 |
| Color             | Dark grey                                                                                                         |
| Height            | 1.89 in (48 mm)                                                                                                   |
| Width             | 1.73 in (44 mm)                                                                                                   |
| Depth             | 2.40 in (61 mm)                                                                                                   |

## Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| Environmental characteristic          | Normal environment           |
| IP degree of protection               | IP2x conforming to IEC 60529 |
| Protective treatment                  | TH IEC 60068                 |
| Ambient Air Temperature for Storage   | -76...176 °F (-60...80 °C)   |
| Ambient Air Temperature for Operation | -40...158 °F (-40...70 °C)   |
| Operating altitude                    | 9842.52 ft (3000 m)          |

## Ordering and shipping details

|                       |                               |
|-----------------------|-------------------------------|
| Category              | 22341-CONTACTOR,D,K,&F ACCESS |
| Discount Schedule     | I12                           |
| GTIN                  | 3389110821864                 |
| Nbr. of units in pkg. | 1                             |
| Package weight(Lbs)   | 2.65 oz (75.0 g)              |
| Returnability         | No                            |
| Country of origin     | FR                            |

## Packing Units

|                              |                          |
|------------------------------|--------------------------|
| Unit Type of Package 1       | PCE                      |
| Package 1 Height             | 1.97 in (5 cm)           |
| Package 1 width              | 1.97 in (5 cm)           |
| Package 1 Length             | 2.56 in (6.5 cm)         |
| Unit Type of Package 2       | BB1                      |
| Number of Units in Package 2 | 10                       |
| Package 2 Weight             | 26.81 oz (760.0 g)       |
| Package 2 Height             | 2.05 in (5.2 cm)         |
| Package 2 width              | 5.12 in (13 cm)          |
| Package 2 Length             | 9.45 in (24 cm)          |
| Unit Type of Package 3       | S03                      |
| Number of Units in Package 3 | 140                      |
| Package 3 Weight             | 24.59 lb(US) (11.155 kg) |
| Package 3 Height             | 11.81 in (30 cm)         |
| Package 3 width              | 11.81 in (30 cm)         |
| Package 3 Length             | 15.75 in (40 cm)         |

## Offer Sustainability

|                            |                                                                                                                                   |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                             |
| California proposition 65  | WARNING: Cancer - www.P65Warnings.ca.gov                                                                                          |
| REACH Regulation           |  <a href="#">REACH Declaration</a>             |
| REACH free of SVHC         | Yes                                                                                                                               |
| EU RoHS Directive          | Compliant  <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                                                               |
| RoHS exemption information |  <a href="#">Yes</a>                           |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a> |

|                             |                                                                                                                              |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------|
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| PVC free                    | Yes                                                                                                                          |
| <b>Contractual warranty</b> |                                                                                                                              |
| Warranty                    | 18 months                                                                                                                    |