

Product datasheet

Specifications



Power supply module, Modicon Premium, input current of 1700mA, secondary power of 75W, 85 to 140VAC and 170 to 264VAC

TSXPSY8500M

! Discontinued

! Discontinued on: 21 Jun 2022

! To be end-of-service on: 31 Dec 2026

Main

Range of product	Modicon Premium Automation platform
Product or component type	Power supply module

Complementary

Primary voltage	100...120 V AC 85...140 V 200...240 V AC 170...264 V
Network frequency	50/60 Hz
Network frequency limits	47...63 Hz
Input current	1700 mA 100 V 500 mA 240 V
Inrush current	30 A 100 V 60 A 240 V
I ² t on activation	15 A ² .s 100 V 8 A ² .s 240 V
I _t on activation	0.15 A.s 100 V 0.15 A.s 240 V
Protection type	Internal fuse 4 A 5 x 20 mm time-delayed primary circuit Overload protection secondary circuit Overvoltage protection secondary circuit Short-circuit protection secondary circuit
Total useful secondary power	100 W at 55 °C with fan module 77 W at 60 °C 85 W at 55 °C
Secondary power	75 W 5 V DC
Current at secondary voltage	1.6 A 24 V DC sensor power supply 15 A 5 V DC
Insulation resistance	>= 100 MOhm primary/ground >= 100 MOhm primary/secondary
Marking	CE
Local signalling	1 LED (green) for presence of sensor voltage (24V) 1 LED (green) for presence of voltages (OK) 1 LED (red) for battery fault (BAT)
Module format	Double
Net weight	0.74 kg

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Immunity to microbreaks	10 ms
Dielectric strength	2000 V primary/earth 2000 V primary/secondary
Standards	CSA C22.2 No 142 73/23/EEC 89/336/EEC 92/31/EEC CSA C22.2 No 213 Class I Division 2 Group D CSA C22.2 No 213 Class I Division 2 Group A UL 508 CSA C22.2 No 213 Class I Division 2 Group C CSA C22.2 No 213 Class I Division 2 Group B IEC 61131-2 93/68/EEC
Product certifications	DNV BV RMRS GL RINA ABS LR
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-25...70 °C
Relative humidity	10...95 % without condensation for operation 5...95 % without condensation for storage
Operating altitude	0...2000 m
Protective treatment	TC
IP degree of protection	IP20
Pollution degree	2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.0 cm
Package 1 Width	18.0 cm
Package 1 Length	26.0 cm
Package 1 Weight	1.026 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)


Use Longer

Lifetime extension	
Repair	No

Dimensions Drawings

Standard and Extendable Racks for Modules Mounting


Dimensions of Modules and Racks



- (1) With screw terminal block modules.
- (2) Maximum depth for all types of modules and their associated connectors.

Connections and Schema

Connecting Power Supply Modules



(1) 24...48Vdc for the TSXPSY5520 supply module.
Provide a protection device and a switch gear upstream of the PLC station.